

3M™ 6000 Series Particulate Filters - 6035 & 6038

Technical Data Sheet



ID 898338
RID 898972

Description

The 3M™ 6000 Series Particulate Filters are a unique design, utilising 3M's proven filter technologies to provide low breathing resistance.

Features

- Solid top design reduces the chance of premature caking, clogging, or soiling with dirt, grime, water or dust
- Protective casing aids decontamination practices
- Patented bonded web technology has more surface area than many standard filters which helps lower breathing resistance making it more comfortable to use
- Unique case making it easy to perform a quick self fit check
- Temperature resistant cover protects filter media from heat, sparks or physical damage
- 3M™ Bayonet Connection System ensures precise and secure locking
- Very lightweight:
 - 6035 Filter is 75 gms per pair of filters
 - 6038 Filter is 95 gms per pair of filters
- Suitable for use with 3M™ Half Face Respirators 6000/6500QL/7500 Series and Full Face Respirators 6000/FF-400 Series

Specifications

The 6000 Series Particulate Filters come in two product options: 3M™ Particulate Filter 6035, P2/P3* and 6038, P2/P3*(HF) both provide protection against dusts, mists and fumes – all particulates.



Materials

The following materials are used in this product:

- Filter Body - Polystyrene
- Gas/Vapour Filter element - Activated Carbon
- Particulate Filter Element - Fibreglass

Standards

Complies with AS/NZS1716:2012 (Respiratory Protective Products)

Use in accordance with AS/NZS 1715:2009 (Selection, use and maintenance of respiratory protective equipment).

Fitting Instructions

Only new, unused filters from their original packaging should be fitted to your facepiece. Ensure that both filters are of the same type and class.

- Align 6000 filter notch with facepiece 3M logo and push together.
- Turn filter 1/4 turn clockwise to stop.
Discard and replace both filters at the same time.
- To remove filter, turn 1/4 turn anticlockwise.

Compatible facepieces



6000 Half Face



6500QL



7500



6000 Full Face



FF-400

Disposal

Dispose in accordance with local and national regulations appropriate to the contaminants captured.

Low boiling point organic compounds are capable of migrating through 3M 6000 filters when not in use.

Technical Specifications

When selected and used in accordance with this standard, is capable of providing protection against particulates at levels up to (10) times the Exposure Standard when used on a half face respirator and up to one hundred (100) times the Exposure Standard when used on a full face respirator and exposures less than the relevant IDLH (Immediately Dangerous to Life and Health) value.

The 6038 is also recommended for use against hydrogen fluoride (HF) up to 30ppm and also offers relief from nuisance** levels of other acid gases such as chlorine or sulphur dioxide and organic vapours.

Markets/Processes

3M™ Particulate Filter 6035, P2/P3*

- Grinding, sanding & polishing
- Food manufacturing
- Construction / quarrying
- Woodworking
- Pharmaceutical/powdered chemicals
- Water blasting
- Fibreglass installation
- Asbestos related tasks (refer to local guidelines***)

3M™ Particulate Filter 6038, P2/P3 (HF)

- Welding
- Pharmaceutical
- As a pickling agent for stainless steel
- Electroplating operations
- Manufacturing of fertiliser
- Etching, frosting of ceramics
- Removal of sand from foundry castings

Warning and Limitations

Particular attention should be given to warning statements where indicated. Proper selection, training, use and appropriate maintenance are essential in order for the product to help protect the wearer from certain airborne contaminants. Failure to follow all instructions on the use of these respiratory protection products and/or failure to properly wear the complete product during all periods of exposure may adversely affect the wearers health, lead to severe or life threatening illness or permanent disability.

Always be sure that the complete product is:

- Suitable for the application;
- Fitted correctly;
- Worn during all periods of exposure;
- Replaced when necessary.

For suitability and proper use follow local regulations, refer to all information supplied or contact an occupational hygienist, safety professional or 3M Customer Services - Australia 1300 363 565 - New Zealand 0800 252 627.

Use this respirator system strictly in accordance with all instructions:

- contained in this booklet,
- accompanying other components of the system.
- Do not submerge the filters in liquid.
- Do not use in atmospheres containing less than 19.5% oxygen. (3M definition. Individual countries may apply their own limits on oxygen deficiency. Seek advice if in doubt).
- Do not use these products in pure oxygen or oxygen-enriched atmospheres.
- Do not use for respiratory protection against atmospheric contaminants/concentrations which have poor warning properties or are unknown or immediately dangerous to life and health (IDLH) or against contaminants/concentrations which generate high heats of reaction with chemical filters.
- Do not use in concentrations above those specified
- Leave the contaminated area immediately if:
 - a) Any part of the system becomes damaged.
 - b) Airflow to the face piece decreases or stops.
 - c) Breathing becomes difficult or increased breathing resistance occurs.
 - d) Dizziness or other distress occurs.
 - e) You smell or taste contaminants or irritation occurs.
- Never alter, modify or repair this device.
- These products do not contain components made from natural rubber latex.
- In case of intended use in explosive atmospheres, contact 3M.

NOTE: Save all user instructions for continuing reference.

Shelf Life, Storage and Transportation

Shelf life of the unopened product is ten (10) years for the 6035 and four (4) years for the 6038 from date of manufacture when stored in temperature range -20°C to +25°C and at less than 80% relative humidity. Average storage conditions may exceed 25°C/80%RH for limited periods. They can reach 38°C/85%RH provided this is for no more than 3 months of the shelf life of the product.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Storing the filters in an airtight container, will reduce exposure to the work environment and help prolong the life of the equipment.

As per AS/NZS1715:2009 Section 4.2.5.3, "All classes of gas filter shall be discarded no longer than six months after opening, irrespective of the number of periods of use".

**Nuisance levels are levels below the relevant Workplace Exposure Standard.
*** Refer to WHS guidelines

Ordering Information

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7000032083	CR180811885	•	•	6035	3M™ Particulate Filters 6035 P3*, 80 EA/Case
7000059883	CR180811893	•	•	6038	3M™ Hydrogen Fluoride Particulate Filter 6038, P3* with Nuisance Level* Organic Vapour and Acid Gas Relief, 20 ea/Pack, 80 ea/Case

*Provides P3 protection only when worn with a 3M Full face Respirator. Provides P2 protection with half face respirator.

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



Technical Statement

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.



3M Australia Pty Ltd
Personal Safety Division
Bldg A, 1 Rivett Road
North Ryde NSW 2113
Customer Service: 1300 363 565
Email: 3msupport.safety.au@mmm.com
Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
94 Apollo Drive, Rosedale
Auckland 0632
Customer Service: 0800 252 627
Email: 3msupport.safety.nz@mmm.com
Web: www.3M.com/nz/ppesafety

3M is a trademark of 3M Company.
© 3M 2025. All rights reserved.