

3M™ Gas and Vapour Filter 6098, AXP3

Technical Data Sheet

Description

The 3M™ Gas and Vapour filter 6098, AXP3 can be used where protection against low boiling point (<65°C) organic compounds and particulates is required. It is designed to be used with 3M Full Face bayonet filter respirators only.

Main Features

- Good balance of weight on face
- Excellent field of vision as a result of unique trapezoidal shape
- Bayonet fitting ensures precise & safer locking to 3M Full Face respirators
- Suitable for use with 3M™ Full Face Respirators 6000/FF-400 Series
- Weight: 395gm per pair of filters

Applications

The 3M Gas and Vapour Filter 6098 can be used in industries where workers will be exposed to low boiling point (<65°C) organic compounds such as Methanol, Acetone or Acrolein. A more complete list of compounds is contained in the Warnings and Use Limitations section. Comes with a P3 particle filter integrated with the cartridge to provide protection from all particulates including highly toxic materials.

Storage and Transportation

Do not store outside the temperature range -10°C to +50°C or with humidity above 90%. When stored as stated, the expected shelf life of the product is 5 years from date of manufacture. End of shelf life (use-by) date is marked on the product and packaging. The original packaging is suitable for transporting the product.

Materials

The following materials are used in this product:

- Filter Body - Polystyrene
- Gas/Vapour Filter element - Activated Carbon
- Particulate Filter Element - Fibreglass



Standards

- Complies with AS/NZS 1716:2012 (Respiratory protective devices).
- Use in accordance with AS/NZS 1715:2009 (Selection, use and maintenance of respiratory protective equipment).

Fitting Instructions

Only new, unused filters from their original packaging should be fitted to your facepiece. Ensure that both filters are of the same type and class.

- A. Align 6098 filter notch with facepiece 3M logo and push together.
- B. Turn filter 1/4 turn clockwise to stop.
Discard and replace both filters at the same time.
- C. To remove filter, turn 1/4 turn anticlockwise.

Disposal

Dispose in accordance with local and national regulations appropriate to the contaminants captured.

The 3M Gas and Vapour Filter 6098 is a SINGLE USE only filter and should be discarded after use. Re-use of 6098 filters may expose the wearer to contaminants previously collected in the filter.

DO NOT immerse product in water, detergent, cleaning fluids etc. **DO NOT** clean the filter using compressed air.

Warnings and Use limitations

Limitations on the use of these filters may differ among countries. 3M recommends the following should be applied in the absence of specific recommendations in Australia and New Zealand.

Low boiling point (<65°C) organic compounds against which the 3M™ Gas and Vapour filter 6098, AXP3 may be used are divided into groups:

- | | |
|----------------|---|
| Group 1 | Low boiling point organic vapours with an Exposure Standard (ES) of less than or equal to 10ppm or which have a short service life. |
| Group 2 | Low boiling point organic vapours with an ES greater than 10ppm |

Against compounds of groups 1 and 2, AX filters complying with AS/NZS 1716 can be used up to the maximum concentrations shown in the table below, **OR** 50 x WES (whichever is the lower concentration), and exposures less than the relevant IDLH (Immediately Dangerous to Life and Health) value.

Group	Maximum Concentration (ppm)	Maximum Usage Time (minutes)
Group1	100 ppm	40 mins
Group 1	500 ppm	20 mins
Group 2	1000 ppm	60 mins
Group 2	5000 ppm	20 mins

- During one 8 hour shift, repeated use of an AX filter is permitted, provided the maximum usage time shown in the table above is not exceeded. The filter **SHOULD NOT** be used on a second shift even if these maximum usage times are not exceeded.
- The use of AX filters against mixtures of low boiling point organic compounds or mixtures of low boiling point compounds and other organic compounds is not permitted as one or more of these compounds may be desorbed from the filter.
- AX filters may be used as A2 filters **ONLY** if no low boiling point organic compound is present. A1 or A2 filters are not to be used against low boiling point organic compounds.

Some examples of Low Boiling point organic compounds are below:

Group1	Group2
Acetaldehyde	n-Pentane
Propanal	Acetone
1,3-Butadiene	Bromoethane
3-Chloro-1-propene	Butane
Diethyl Amine	Chloroethane
Dimethyl ether	Cyclopentadiene
1,1-Dimethylethylamine	Dibromodifluoromethane
Ethanethiol	Diethyl ether
Iodomethane	Dimethyloxymethane
Methanol	Ethylformate
2-Propenal (Acrolein)	Methyl Acetate
Vinyl Chloride	Methyl propane

Proper selection, training, use and appropriate maintenance are essential in order for the product to help protect the wearer from certain airborne contaminants. Failure to follow all instructions on the use of these respiratory protection products and/or failure to properly wear the complete product during all periods of exposure may adversely affect the wearer's health, lead to severe or life threatening illness or permanent disability.

Always be sure that the complete product is:

- Suitable for the application;
- Fitted correctly;
- Worn during all periods of exposure;
- Replaced when necessary.

For suitability and proper use follow local regulations, refer to all information supplied or contact an occupational hygienist, safety professional or 3M Customer Services - Australia 1300 363 565 - New Zealand 0800 252 627.

- Do not submerge the filters in liquid.
- Do not use these products in flammable or explosive atmospheres.
- Do not use in atmospheres containing less than 19.5% oxygen. (3M definition. Individual countries may apply their own limits on oxygen deficiency. Seek advice if in doubt).
- Do not use for respiratory protection against atmospheric contaminants/concentrations which have poor warning properties or are unknown or immediately dangerous to life and health (IDLH) or against contaminants/concentrations which generate high heats of reaction with chemical filters.
- Do not use these products when working with open flames or liquid metal droplets.
- Do not use these products in pure oxygen or oxygen-enriched atmospheres.
- Do not use in concentrations above those specified in **Warning and Use Limitations**.
- In case of intended use in explosive atmospheres, contact 3M Technical.
- Leave the contaminated area immediately if:
 - D. Any part of the system becomes damaged.
 - E. Airflow to the face piece decreases or stops.
 - F. Breathing becomes difficult or increased breathing resistance occurs.
 - G. Dizziness or other distress occurs.
 - H. You smell or taste contaminants or irritation occurs.
- Never alter, modify or repair this device.
- These products do not contain components made from natural rubber latex.

Shelf Life, Storage and Transportation

Shelf life of the unopened product is five (5) years from date of manufacture when stored in temperature range -10°C to +50°C and at less than 90% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Storing the filters in an airtight container, will reduce exposure to the work environment and help prolong the life of the equipment.

Additional Information

3M™ Organic Vapour Monitor 3500+ and 3501+

3M™ Monitors are simple and effective personal sampling badges. The monitor captures a wide range of airborne organic vapours, enabling a laboratory to analyse and identify the type and level of exposure to the worker.

The 3M™ Organic Vapor Monitors 3501+ higher sampling rate badge is for low concentrations or short term exposure limit (STEL) sampling. It is designed to measure time weighted-average (TWA) or short term exposure limit (STEL) exposure to volatile organic chemicals to demonstrate compliance with Occupational Exposure Limits (OELs).

For more information, please contact 3M and request a copy of the 3M™ Organic Vapour Monitor 3500+ and 3501+ Tech Data Sheet.



3M™ Select & Service Life Software

3M have designed software to help you estimate how frequently certain 3M™ Gas and Vapour Cartridges should be replaced. You can then use this information to establish a cartridge change schedule. You will firstly need information on the chemical contaminants in your working environment.

The exposure monitoring data may be entered into the 3M Service Life software at www.3M.com/sls to estimate the service life of 3M gas/vapour cartridges.

For more information contact your 3M representative.



For assistance in determining 3M bayonet gas/vapour cartridge breakthrough and filter change schedules for certain gas/vapour contaminants visit the free

3M Select and Service Life (SLS) Software | www.3m.com/sls

Ordering Information

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7000021315	70071617974	•	•	6098	3M™ Organic Vapour and Particulate Cartridge Filter 6098, AXP3, 4 ea/Pack, 32 ea/Case. For Organic Vapours with <65 degrees celsius boiling point. For use with Full Facepieces only

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

SCAN OR CLICK FOR:



Reusable
Respirator
Catalogue Section



Full Personal
Safety Division
Catalogue

Technical Statement

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.



3M Australia Pty Ltd
Personal Safety Division
Bldg A, 1 Rivett Road
North Ryde NSW 2113
Customer Service: 1300 363 565
Email: 3msupport.safety.au@mmm.com
Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
94 Apollo Drive, Rosedale
Auckland 0632
Customer Service: 0800 252 627
Email: 3msupport.safety.nz@mmm.com
Web: www.3M.com/nz/ppesafety

3M is a trademark of 3M Company.
© 3M 2025. All rights reserved.