



Technical Data Sheet

R9601

APR 2019 (V6)

Product Description R9601 is a pressure sensitive hot melt adhesive which is used in melted form. This adhesive can provide strong bonding with relatively flexible form. It is suitable for many kinds of substrate such as metal, some plastics, paper, fabric, foam, non-woven, wood and other difficult substrate. This adhesive also provides very high tack properties when it is wet but low tack when it is dry.

Features

- Plastic part attachment
- Cushion bonding
- Sealing application
- Plastic & paper bonding

Product Construction	Adhesive Type	Synthetic Based Thermoplastic Hot Melt
	Appearance	Water light – light yellow
	Viscosity	1700 +/- 500cps (Brookfield RVT 27/20/160°C)
	Softening Point	85 ± 5°C (Ring & Ball)
	Open Time	N/A (pressure sensitive adhesive)
	Working Temperature	130 – 160° Celsius

Application Technique Nozzle

Shelf life 12 months from date of manufacture when stored in original cartons at 21° -25° Celsius and maximum 50% relative humidity

Important Notice 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application

Limitation of Liability Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**3M Indonesia
Industrial Adhesives & Tapes Division**

Perkantoran Hijau Arkadia, Tower F, 8th Floor
Jl. TB. Simatupang Kav. 88 Jakarta Selatan 12520 - Indonesia
Tel: 62 21 29974000