

**3M** Science.  
Applied to Life.™

# Construction tough tape. Quick stick and easy removal.

## 3M™ High Performance Flatback Tape 2519

This versatile tape is now on the construction scene. It offers a great solution for covering seams on temporary floor protection. Plus, it's easy to work with.

- Easy unwind and hand tearable for fast, easy application to floor protection materials
- High strength paper backing and natural rubber adhesive provide reliable seam sealing
- Smooth finish minimizes tripping hazard
- Go-to pricing you'll get stuck on



# 3M™ High Performance Flatback Tape 2519

Temporary adhesion to the following construction materials:

- Painters' board
- Masonite
- Plywood
- Rosin paper
- Builders foam
- Cardboard
- Fiberboard
- Masonite
- Plastic sheeting

**Not intended to be directly applied to the original flooring.**

Backing: Unbleached kraft paper

Adhesive: Rubber

Tape thickness: 7.3 mils (0.19 mm)

Temperature use range: up to 200°F



**3M™ Applicator M-1**  
Helps apply tape to floors quickly, easily and perfectly.  
UPC 0-00-511158-08869  
3M ID 70006758950

UPC	Product ID	Color	Size	Case	Units
0-00-51128-98283-9	XG700013954	Tan	24 mm x 55 m	36	RL
0-00-51128-98284-6	XG700013962	Tan	36 mm x 55 m	24	RL
0-00-51128-99446-7	XG700013798	Tan	48 mm x 55 m	24	RL
0-00-51128-99447-4	XG700013806	Tan	72 mm x 55 m	12	RL
0-00-51128-99448-1	XG700013714	Tan	96 mm x 55 m	8	RL
0-00-54007-99938-6	XG700014184	Tan	144 mm x 55 m	8	RL
<b>Longer length rolls</b>					
0-00-76308-86674-7	70007506846	Tan	144 mm x 110 m	8	RL
0-00-76308-86673-0	70007506838	Tan	96 mm x 110 m	12	RL
0-00-76308-86672-3	70007506820	Tan	72 mm x 110 m	12	RL
0-00-76308-86671-6	70007506812	Tan	48 mm x 110 m	24	RL
0-00-76308-86670-9	70007506804	Tan	36 mm x 110 m	24	RL

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



## Closure and Masking Systems Division

Building 225-3S-06  
St. Paul, MN 55144-1000  
Phone 1-800-362-3550  
Fax 1-877-369-2923  
Web [www.3M.com/tape](http://www.3M.com/tape)

3M and 3M Science Applied to Life are trademarks of 3M Company.  
© 3M 2019. All rights reserved. (Janz v2 9/19)  
70-0716-9783-6