


Conversion guide for 3M™ Secure Click™ Half Facepiece Reusable Respirator HF-800 Series.

Designed with smart and intuitive features, the 3M™ Secure Click™ Half Facepiece Reusable Respirator helps protect workers from particulates and a wide variety of gases and vapours when used with approved 3M™ Secure Click™ Filters and Cartridges shown below.

Note: initial offering shown (watch for more to follow).





	Gas and Vapour Cartridges			Combination Cartridges		
Bayonet Connection	6001 OV	6003 OV/AG	6006 MG/V	60921 OV/P100	60923 OV/AG/P100	60926 MG/V/P100
3M [™] Secure Click [™] Connection	D8001 OV	D8003 OV/AG	D8006 MG/V	D80921 OV/P100	D80923 OV/AG/P100	D80926 MG/V/P100

	P95 Particulate Filters			P100 Particulate Filters		
Bayonet Connection	20 WOGH / Put Bo. 15,062 105 Pat Bo. 15,062 1077-24 07	2076HF*	2078**	2091	2000 12.1123 0007 2096*	2007***
3M [™] Secure Click [™] Connection	3M D 3071 (P35) If garage 1 Managama (18 00 (100)) D3071	3M 03076HF (P55) (P3076HF*	3MD3078 1995 199	3M D3091 (**100) M SECTION (**100) D3091	MD3096 (P160) (P	3M D3097***

	20071	50010	20001		20007
	P100 Particulate Fil	Replaceable Particulate Filters and Retainer			
Bayonet Connection	7093 / 7093B	7093C / 7093CB	30 Servi scoto (SEE) erecurring e	### Note: ⊕ ***********************************	501 Filter Retainer
3M [™] Secure Click [™] Connection	D9093 / D9093B	D9093C OV/AG / D9093CB	JAM D7N11 NIOSH N95 B19199) Micronipatants This side out Ce color vers l'existiceur Este lado hacie stuere	3M D7P71 NIOSH P95 819:301 Microelysteets This dide out Ge cotte vera Practicus Este lade hacis sfuers	D701 Filter Retainer

- * 3M recommended for relief against nuisance levels of acid gases. Nuisance level acid gas refers to concentrations less than the OSHA PEL or applicable government occupational exposure limits, whichever is lower.
- **3M recommended for relief against nuisance levels of acting gases. Nuisance level or gases. Nuisance level or gases in the Control of the C



AWARNING

These respirators help protect against certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. A written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in sickness or death. For correct use, see supervisor and User Instructions, or call 3M PSD Technical Service in Canada at 1-800-267-4414 and in USA at 1-800-243-4630.