

Usage Details

All surfaces must be considered contaminated and must be cleaned prior to application of film or decals. Wash the surface with detergent and water to remove heavy road dirt.
Dry the surface with a soft clean cloth.
Saturate a clean cloth with 3M Surface Preparation System.
Wipe the entire surface with 3M Surface Preparation System.
Do not use a dirty cloth. Change cloth frequently.
Dry off the cleaned surface with a soft cloth until the surface is completely clean and dry.
Make sure solvents have evaporated prior to application. Trapped solvents may effect the adhesion of films or decals.
In the area of rivets and seams, liquid retention can cause capillary action. Use a heat gun on rivets to dry out retained liquid.

Limitations of End Uses

3M specifically does not recommend or warrant the following uses, but please contact us to discuss your needs to recommend other products.

Substrates other than recommended.

Remarks

This bulletin provides technical information only.

Important notice All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.
Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Additional information Visit the web site of your local subsidiary at www.3Mgraphics.com for getting:
- a complete product overview about materials 3M is offering



Commercial Solutions Division
Hermeslaan 7
1831 Diegem, Belgium

Responsible for this technical bulletin

3M Deutschland GmbH
Carl-Schurz-Str. 1
41453 Neuss, Germany

3M is a trademark of 3M Company. All other trademarks are the property of their respective owners.

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.