



3M Science.
Applied to Life.™

Water-based. Fast paced. Durable label printing.

Optimize your water-based inkjet printing.

3M™ Performance Label Materials, Water-Based Inkjet Printable

Introducing the water-based inkjet printing film labels you've been waiting for. 3M™ Performance Labels let you print with great resolution at a low cost per area. It's the durable label stock you can count on to enhance your digital messaging.

- ▶ More durable than paper-based labels
- ▶ No additional topcoating or priming needed for print receptivity
- ▶ UL recognized with several different water-based inkjet systems*
- ▶ BS5609, Section 3 compliant material**



Product Name	3M ID	Dimensions	Facestock	Adhesive	Liner	Suggested Applications	
PG0305	7100200188	Configurable Roll	Matte White Polyester (3 mil)	G1120 (1.8 mil)	50# SC	Full color tire tread labeling.	
7882-IJ	7100222007	4.5 in. x 1668 ft.		400 (0.8 mil)	55# DK	Wide temperature range designed for use in medical applications.	
	7100222288	9 in. x 1668 ft.					
	7100210601	Configurable Roll					
7850-IJ	7100202548	Configurable Roll		350 (1.1 mil)		Harsh industrial environment labeling applications.	
	7100222074	4.5 in. x 1668 ft.					
	7100222003	9 in. x 1668 ft.					
7790-IJ	7100202547	Configurable Roll	Polyolefin (5 mil)			GHS/Drum Labeling. BS5609, Section 3 compliant material.	
	7100221363	4.5 in. x 1668 ft.					
	7100221347	9 in. x 1668 ft.					
FP033-IJ	7100214285	Configurable Roll			P1480 (1.4 mil)	50# SC	Emulsion adhesive for industrial labeling applications.

*See UL file MH16411 in UL Product iQ™ (Certifications Search) at ul.com for specific details.

**See chart above for specific products meeting BS5609.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. **Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and **exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.** **Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Industrial Adhesives and Tapes Division
3M Center, Building 225-55-14
St. Paul, MN 55144-100 USA

Phone 800-422-8116
Web 3M.com/DurableLabels

© 3M 2020. All rights reserved. 3M is a trademark of 3M. Images used with permission of Epson America, Inc. All other trademarks are property of their respective owners.
Printed in U.S.A. 70-0713-4610-3