



## Automotive Aftermarket Division

### 3M™ Scotch™ 218 Fine Line Masking Tape

---

#### 1) Part Numbers

06520 – 3mm x 55m  
06521 – 6mm x 55m  
06522 – 6mm x 55m  
06523 – 6mm x 55m

#### 2) Description and end uses

Scotch™ 218 Fine Line Masking tape is an olive green coloured, more specialised tape for applications requiring fine two-tone or paint stripping work.

Developed to be conformable but without excessive stretch, enables the tape to maintain a superior paint edge. Its low tack adhesive makes it ideal for masking on fresh paint without leaving an imprint on the surface.

Satisfactory performance and clean removal of Scotch™ Tape 218 will be achieved at varying temperatures/time exposure on many substrates. Tests should be conducted to establish Scotch™ Tape 218 performance parameters in your process conditions. The optimum level for product performance and easy removal is at 90 °C for 60 min.

Note: For detail masking of components we would recommend 3M™ 471T Fine line masking tape as a better alternative.

Features	Advantages	Benefits
* Film backing	* Excellent conformability	* Ideal for design/ two-tone work
	* Smoothness	* Minimizes chance of imprint damage
	* Solvent and moisture resistance	* Prevents paint bleed through
	* Thinness	* Excellent paint line
	* Easy tear	* Good handling
	* Good paint anchorage	* Paint flaking resistance

---



# Technical Data Sheet

Effective: 28/02/2020 Supersedes: 01/12/1995

* Rubber resin adhesive	* Instant adhesion	* Adheres easily
	* Good holding power	* Resists lifting
	* Adhesive transfer resistance	* Clean removal
	* Controlled unwind	* Easy to use

As well as the vehicle refinish market, Scotch™ 218 tape can be used for a wide range of applications such as, circuit board conformal coat masking, moisture or solvent resistant masking, lettering and silk screen masking.

This tape can withstand a temperature of 90 °C for one hour.

### 3) Physical Properties

Thickness : 0.120 mm AFERA 4006  
Adhesion to steel : 11 N/25 mm AFERA 4001  
Tensile strength : 57 N/25 mm AFERA 4004  
Elongation : 490 %AFERA 4005  
Temperature performance : 90 °C

### 4) Directions for Use

1. Ensure that the area/substrates to be masked is clean and dry prior to the application of the tape.
2. Window rubbers and plastic mouldings should be cleaned using a silicon remover / mild solvent to ensure they are free from contamination to improve the tapes adhesion.

### 5) Storage

Store in clean dry place. Temperature of 21°C and 50 percent relative humidity are recommended.

### 6) Safety

1. When using solvents etc. for cleaning the surface prior to the masking, care must be taken to avoid contact with the skin and eyes. The correct PPE must be worn at all times.
2. After removing the 218 Fine Line Masking Tape from the vehicle, as it may now be contaminated with paint waste it should be disposed of in accordance to local authority / country legislation.

**3M™ Automotive Aftermarket Products are designed FOR PROFESSIONAL USE ONLY.**



# Technical Data Sheet

Effective: 28/02/2020 Supersedes: 01/12/1995

## 7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

### For Additional Health and Safety Information

3M South Africa & Sub-Saharan Africa, 146A Kelvin Drive, Woodmead, Sandton, South Africa, Tel: (0861) 225536
3M (East) AG Representation Office Tirane, Rruga Sami Frasherri, Pallati i Ri Perxhola Kati 2 Ap2, 1000 Albania
3M Arabia, LLC, Building 24-25 3M Saudi Arabia Zone C, Business Gate, Airport Road, Riyadh, Saudi Arabia
3M Bulgaria, Mladost 4, Business Park, bl.4, 2nd floor, Sofia 1766, Bulgaria
3M Česko, spol. s r.o., V Parku 2343/24, 148 00 - Praha 4, Czech Republic
3M (East) AG, Branch office Croatia, Avenija Većeslava Holjevca 40, 10 000 Zagreb, Croatia, Tel: +385 1 2499750, www.3m.com.hr
3M Egypt, Finance Center , New Cairo , Plot 140 , Banking Sector , 5th settlement , Cairo , Egypt
3M Hellas MEPE, Automotive Aftermarket Division, 20 Kifisias Avenue, 151 25 Marousi, Greece, Phone: +30 210 68 85 300, innovation.gr@mmm.com, www.3M.gr
3M Hungária Kft, Neumann János u. 1/E, 1117 Budapest, Hungary
3M Israel, 91 Medinat Hayehudim St., Herzliya, Israel
3M Kenya Ltd, Victoria Towers, 3rd Floor, Kilimanjaro Av, Upperhill, Kenya
3M Gulf Limited, Ein El Mreisseh, Saint Charles City Center, 4th. Floor, P.O.Box: 11-5025, Riad el Solh, Beirut 1107 2180 Lebanon
3M Minnesota Mining & Manufacturing Nigeria Limited, No 2 Sheraton Opebi Link Road, Ikeja, Lagos Nigeria
3M Pakistan, Islamic Chamber of Commerce Building, ST-2/A, Block 9, KDA Scheme 5, Clifton, Karachi, Pakistan
3M Poland, Al. Katowicka 117, Kajetany, 05-830 Nadarzyn, Poland, Telefon: +48 22 739 60 00, www.3m.pl/kontakt
3M Gulf (Representation Office), Suhaim Bin Hamad St., Al Mana Towers Tower B, 2nd Floor, Office No.4, Doha Qatar, P.O.Box 14685
3M Romania, 12 Menuetului St., Bucharest Business Park, Building D, District 1 013713 Bucharest, Romania
3M (East) AG, Representation Office Serbia, Airport City, Omladinskih brigada 90B, 11070 Belgrade, Serbia, Tel: +381 11 2209 400, www.3m.co.rs/3M/sr_RS/3m-south-east-europe/
3M Slovensko s.r.o., Polus Tower 2, Vajnorská 100/B, 83104 Bratislava
3M (East) AG, Branch office Slovenia, Cesta v Gorice 8, 1000, Ljubljana, Slovenia, Tel: +386 1 2003 630, www.3m.com/3M/sl_SI/3m-south-east-europe/



# Technical Data Sheet

Effective: 28/02/2020 Supersedes: 01/12/1995

3M Sanayi ve Ticaret As, Barbaros Mah., Mor Smbl Sok., No:7/3F, 27-51, Nidakule Ataehir Gney, 34746 Ataehir, İstanbul, Turkey
---

3M Gulf Limited, Dubai Internet City, Building No. 11, 3rd Floor, U.A.E
---

© 3M 2019. 3M and Scotch are trademarks of the 3M company. All rights reserved