

Effective: 28/02/2020 Supersedes: 01/08/2003

Automotive Aftermarket Division

3M[™] Scotch® Clear Masking Films

1) Part Numbers

07838 80110

2) Description and end uses

Scotch™ Film 07838 and 80110 is a clear masking film designed for all gross masking purposes in the refinish industry. Its static properties hold the film in place allowing large areas of a vehicle that do not require painting to be protected from overspray quickly and accurately.

Sizes available: 07838 - 4m width x 150m length 80110 - 5m width x 120m length

The temperature resistance of up to 115°C for one hour allows the film to be used with all types of curing /drying methods, including conventional low bake and Infra-Red lamps and ovens.

Features	Advantages	Benefits
High density polyethylene film (HDPE)	 Excellent paint, solvent and water resistance Good temperature performance Good conformability 	 No bleed through Allows repeated bake cycles Easy handling (saves time)
	Easy to cut and trim	 Nice and easy handling (saves time)
Specially treated	Very good paint anchorage	 No need for using paper on the surroundings of the area to be repaired
Translucent	Neutral colour	 Very easy to identify where the film should be trimmed



Effective: 28/02/2020 Supersedes: 01/08/2003

3) Physical Properties

Thickness : 0.0114 mm AFERA 4006 Tensile strength (machine direction) : 17N/25 mm AFERA 4004

Tensile strength (cross direction) : 10N/25 mm AFERA 4004

Temperature performance : 115°C

Satisfactory performance of the Scotch™ Clear Masking Film may be achieved at varying temperatures/time exposure on many substrates. Tests should be conducted to establish Scotch™ Film 07838 performance parameters in your process conditions.

4) Directions for Use

- 1. Ensure that the film is used the correct way around on the vehicle prior to paint application. To achieve this make sure that when the film is placed on the vehicle the '3M' logo and the 'Paint this side' printed onto the surface of the film reads correctly and are not reversed. Failure to do so may result in rework.
- 2. The vehicle should be as dry as possible prior to masking to avoid any damp being trapped under the film during the baking/drying process.

Note: We would advise that if any areas of damp are noticed prior to the baking process, the film be slit with the appropriate cutter to allow the moisture to escape.

- 3. When used in conjunction with the dedicated 3M[™] Masking film dispenser (PN: 50872), the film can be applied quickly and easily to the entire vehicle by one person, saving time and money.
- 4. Care must be taken when cutting the film around the areas to be painted, not to scratch or damage the vehicle.

5) Storage

Store in clean dry place. Temperature of 21°C and 50 percent relative humidity are recommended.

6) Safety

3M[™] Automotive Aftermarket Products are designed FOR PROFESSIONAL USE ONLY



Effective: 28/02/2020 Supersedes: 01/08/2003

Always use the product in the manner in which it is designed to be used.

Ensure the correct PPE must be worn at all times.

When removing the masking film after use from the vehicle, it should be disposed of following local authority/ country guidelines.

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

For Additional Health and Safety Information

3M South Africa & Sub-Saharan Africa, 146A Kelvin Drive, Woodmead, Sandton, South Africa, Tel: (0861) 225536

3M (East) AG Representation Office Tirane, Rruga Sami Frasheri, Pallati i Ri Perxhola Kati 2 Ap2, 1000 Albania

3M Arabia, LLC, Building 24-25 3M Saudi Arabia Zone C, Business Gate, Airport Road, Riyadh, Saudi Arabia

3M Bulgaria, Mladost 4, Business Park, bl.4, 2nd floor, Sofia 1766, Bulgaria

3M Česko, spol. s r.o., V Parku 2343/24, 148 00 - Praha 4, Czech Republic

3M (East) AG, Branch office Croatia, Avenija Većeslava Holjevca 40, 10 000 Zagreb, Croatia, Tel: +385 1 2499750, www.3m.com.hr

3M Egypt, Finance Center, New Cairo, Plot 140, Banking Sector, 5th settlement, Cairo, Egypt

3M Hellas MEPE, Automotive Aftermarket Division, 20 Kifisias Avenue, 151 25 Marousi, Greece,

Phone: +30 210 68 85 300, innovation.gr@mmm.com, www.3M.gr

3M Hungária Kft, Neumann János u. 1/E, 1117 Budapest, Hungary

3M Israel, 91 Medinat Hayehudim St., Herzliya, Israel

3M Kenya Ltd, Victoria Towers, 3rd Floor, Kilimanjaro Av, Upperhill, Kenya

3M Gulf Limited, Ein El Mreisseh, Saint Charles City Center, 4th. Floor, P.O.Box: 11-5025, Riad el Solh, Beirut 1107 2180 Lebanon

3M Minnesota Mining & Manufacturing Nigeria Limited, No 2 Sheraton Opebi Link Road, Ikeja, Lagos Nigeria

3M Pakistan, Islamic Chamber of Commerce Building, ST-2/A, Block 9, KDA Scheme 5, Clifton, Karachi, Pakistan

3M Poland, Al. Katowicka 117, Kajetany, 05-830 Nadarzyn, Poland, Telefon: +48 22 739 60 00, www.3m.pl/kontakt

3M Gulf (Representation Office), Suhaim Bin Hamad St., Al Mana Towers Tower B, 2nd Floor, Office No.4, Doha Qatar, P.O.Box 14685

3M Romania,12 Menuetului St., Bucharest Business Park, Building D, District 1 013713 Bucharest, Romania



Effective: 28/02/2020 Supersedes: 01/08/2003

3M (East) AG, Representation Office Serbia, Airport City, Omladinskih brigada 90B, 11070 Belgrade, Serbia, Tel: +381 11 2209 400, www.3m.co.rs/3M/sr_RS/3m-south-east-europe/

3M Slovensko s.r.o., Polus Tower 2, Vajnorská 100/B, 83104 Bratislava

3M (East) AG, Branch office Slovenia, Cesta v Gorice 8, 1000, Ljubljana, Slovenia,

Tel: +386 1 2003 630, www.3m.com/3M/sl_SI/3m-south-east-europe/

3M Sanayi ve Ticaret As, Barbaros Mah., Mor Sümbül Sok., No:7/3F, 27-51, Nidakule Ataşehir Güney, 34746 Ataşehir, İstanbul, Turkey

3M Gulf Limited, Dubai Internet City, Building No. 11, 3rd Floor, U.A.E

© 3M 2019. 3M and Scotch are trademarks of the 3M company. All rights reserved