

8 7 6 5 4 3 2 1

3M™ HIGH FLEX CABLE, ROUND CONDUCTOR, 3250 SERIES
1.0 mm 28 AWG STRANDED, PVC

Regulatory: For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: For industrial use only. Not intended, labeled or packaged for consumer sale or use.

3M Company
Electronics Materials Solutions Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753-5380
1-800-225-5373
www.3M.com/interconnect

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
http://www.3M.com/interconnect

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373

REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
B	112428	FEB 09, 2024 REMOVE CONDUCTOR COUNTS	JNC	FJR
A	85634	JUL 30, 2019 PRODUCTION RELEASE	JNC	RLI
DESIGN REFERENCE	NEXT ASSEMBLY	DRFT	CHKD	DATE
CASTIGLIONE		JUL 03, 2019		
CHKD	DATE	APPRV	DATE	
J. GEISSINGER	JUL 30, 2019	RON IMKEN	JUL 12, 2019	
DIVISION	DIVISION CODE	© 3M COPYRIGHT 2024		
EMSD		This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.		
DO NOT SCALE DRAWING	SCALE 8/1	TOLERANCES EXCEPT AS NOTED	3M Center St. Paul, MN 55144	
THIRD ANGLE PROJECTION	INCHES	.00 ±	TITLE	
INTERPRET PER ASME Y14.5 - 2018	MILLIMETERS	.000 ±	HIGH FLEX CABLE, RD CONDUCTOR, 3250 SERIES, 1.0MM, 28AWG	
MAX SURFACE ROUGHNESS	0 ±	.000 ±	CAGE NUMBER	DRAWING NO.
MARKED ONLY	0 ±	.000 ±	D78-5100-2694-7	REV. B
	ANGLES	0 ±	MODEL	3250
			DET	SHT 2 OF 2

78-5100-2694-7
DRAWING NUMBER