Description

The 3M™ Defoamer is a concentrated product designed to minimize or eliminate foaming problems caused by certain cleaning processes.

Special Features

- Breaks down and eliminates foam on contact
- Fast acting foam control allows more liquid to be collected in the recovery tank before emptying
- Works in the recovery tanks of most equipment

Applications

- Recovery tanks of autoscrubbers
- Recovery tanks of extraction equipment

Packaging

- One gallon plastic bottle
- Four bottles per case

General Use Directions

Refer to the 3M[™] Defoamer SDS for personal protective equipment recommendations.

- 1. Shake container well before using.
- 2. Pour defoamer directly into the recovery tank.
- 3. Use approximately 1 oz of defoamer per gallon of recovery tank capacity.

NOTE

Add more defoamer as necessary to control foam. Do NOT add defoamer to the solution tank.

Health and Safety

Tools and Equipment Usage

When using any equipment, always follow the manufacturer's instructions for safe operation.

Chemicals

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety, and environmental information.

Follow this link to obtain SDS sheets for 3M products.

Follow this link to obtain information about substances of very high concern (SVHC) for EU products.

NOTE

Refer to the product's safety data sheet for specific physical property, health hazard, first aid, and precautionary information.

3M™ Defoamer

• 18-1526-5



Warranty Information

Technical Information

Technical information, guidance, and other statements provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license to any intellectual property rights is granted or implied with respect to this technical information.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment, reviewing all applicable regulations and standards, and reviewing the product label and use instructions. Failure to properly evaluate, select, and use a 3M product in accordance with instructions or to meet all applicable safety regulations may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



All other trademarks are property of their respective owners. Revision B, October 2024 Please recycle.