

## Trizact™ Abrasive Belt 347FC

## **Product Data Sheet**

Date 02/20209 Supersedes: NEW

٠		

3M I.D. Number	347FC	
Product Description	3M™Trizact™CF 347FCpolishing belts are specifically designed for high-pressure, machinepolishing operations. This product is designed to be run wet or dry and does have a grinding aid.	
Mineral	Aluminum Oxide	
Grain	A300, A160, A100, A65, A45, A30	
Bond	Resin bonded	
Backing	Polyester X-weight	
Storage	Store at 16 °C – 26 °C and 35-50 % relative humidity in its original box on "first-in - first-out" cycle.  Note: The shelf life may be shortened if the original packaging is not properly sealed or stored in an environment with high temperatures or humidity.	
Precautionary Information	Refer to Product Label and Safety Instruction Leaflet for health and safety information before using the product.  For information please contact your local 3M Office.  www.3M.com	
For Additional Information	To request additional product information or to arrange for sales assistance, call your local 3M Application Engineering.	
Important Notice		

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company

## 3M Nederland B.V.

Abrasives Systems Division Molengraaffsingel 29 2629 JD Delft NEDERLAND

www.3M.nl/abrasives