



Scotch-Brite™ Bristle Brush

Product Data Sheet

Date 05_2019
Supersedes: -

Product Name	Bristle Brush: BB-ZB			
Product Description	<p>Scotch-Brite Bristle products are injection molded with the abrasive mineral distributed throughout the nylon material for a 3-dimensional product. They are used for:</p> <p>Deburring – Removing small burrs in difficult to reach areas Blending – Refining or generating a grain pattern on a part Cleaning – Removing surface contaminants, rust, adhesive, weld burn Coating Removal – Removing paint, primer, and other coatings</p>			
Mineral	<p>Ceramic: 36, 50, 80, 120</p> <p>Aluminium Oxide: 220, 400, 6 Micron, 1 Micron</p> <p>Pumice: Pumice</p>			
Fibre/	Nylon			
Grades	Grade	Mineral	Style	Color
	36	Ceramic/Al Ox Blend	TA	Brown
	50	Ceramic/Al Ox Blend	TA	Green
		Ceramic	TS	Green
	80	Ceramic/Al Ox Blend	TA/TC	Yellow
		Ceramic	TC/TS	Yellow
	120	Ceramic/Al Ox Blend	TC	White
		Ceramic	TS/TC	White
	220	Aluminum Oxide	TC	Red
	400	Aluminum Oxide	TC	Blue
	6 Micron	Aluminum Oxide	TC	Peach
	1 Micron	Aluminum Oxide	TC	Lt. Green
	Pumice	Pumice	TC	Pink
Bristle Design	<p>TA – Angled, the most aggressive Bristle design TS – Straight, can be ran either direction, TC – Curved, the softest Bristle design. TA and TC must be run with the in the direction of the Bristle angle.</p>			
Identification	<p>All relevant product identification information can be found on the product label or on the box in which the product was received or on the with the product supplied Safety Instruction Leaflet.</p>			

<p>Recommended (Ideal) Storage Conditions</p>	<p>Store under “first-in - first-out” base and at recommended conditions (16-26°C/ 35-50% rH). Temperature and humidity beside these conditions should be avoided.</p>
<p>Safety</p>	<p>Refer to Product Label and Safety Instruction Leaflet for health and safety information before using the product.</p> <p>Always use appropriate PPE and follow safety precautions as instructed in the associated Product Safety Insert. Product Safety Inserts are included with shipped product and are also available on-line through 3M.com</p> <p><u>This product needs to be used with accessories 3M Roloc™ Disc Pads, Type TR, TS or TSM and 3M Disc Pad Holders (Hook-and-Loop) as indicated.</u></p> <p>For information please contact your local 3M Office. www.3M.com</p>
<p>For Additional Information</p>	<p>To request additional product information or to arrange for sales assistance, call your local 3M Application Engineering</p>
<p>Important Notice</p>	<p>All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law</p>
<p>Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations</p>	

3M is a trademark of the 3M Company

3M Nederland B.V.
 Abrasives Systems Division
 Molengraaffsingel 29
 2629 JD Delft
 NEDERLAND

www.3M.nl/abrasives