



Scotch-Brite™ Clean and Strip XT Pro Disc

Product Data Sheet

Date 04_2019
Supersedes: -

3M I.D. Number	Scotch-Brite™ Clean and Strip XT Pro Disc Scotch-Brite™ Roloc™ Clean and Strip XT Pro Disc Scotch-Brite™ Roloc™+ Clean and Strip XT Pro Disc Scotch-Brite Roloc™ Pro Brake Hub Cleaning Disc
Product Description	Nonwoven Abrasive Disc for cleaning, finishing, polishing, blending, scuffing, deburring and paint stripping.
Mineral	Extra Coarse (XCS) grade of aluminum oxide
Construction	Nonwoven web of randomized fibers bonded together and coated with abrasive mineral
Dimensions	Diameters: 50.8, 76.2mm and 100mm Roloc™ TR 115 and 180mm TN Quick Change 115 and 180mm Type 27 115, 125 and 180mm Type 27 Quick Change 100mm single ply and double ply shaft mount 100mm single ply and double ply Roloc™+ 100 x 6,35mm, 150 x 12,7mm, and made to order Center Hole Disc 38,1 x 15,8mm Brake Hub Cleaning Disc
Identification	All relevant product identification information can be found on the product label or on the box in which the product was received or on the with the product supplied Safety Instruction Leaflet.
Recommended (Ideal) Storage Conditions	Store under “first-in - first-out” base and at recommended conditions (16-26°C/ 35-50% rH). Temperature and humidity beside these conditions should be avoided.

Safety	<p>Please refer to all local safety and industrial standards.</p> <p>Always use appropriate PPE and follow safety precautions as instructed in the associated Product Safety Insert. Product Safety Inserts are included with shipped product and are also available on-line through 3M.com</p> <p><u>This product needs to be used with accessories 3M Roloc™ Disc Pads, Type TR, TS or TSM, Scotch-Brite™ Mandrel MN-AC and 3M Disc Pad Holders (Hook-and-Loop) as indicated.</u></p> <p>For information please contact your local 3M Office. www.3M.com</p>
For Additional Information	<p>To request additional product information or to arrange for sales assistance, call your local 3M Application Engineering</p>
Important Notice	<p>All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law</p>
<p>Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations</p>	

3M is a trademark of the 3M Company

3M Nederland B.V.
Abrasives Systems Division
Molengraaffsingel 29
2629 JD Delft
NEDERLAND

www.3M.nl/abrasives