



Scotch-Brite™ EXL Unitized Wheel

Product Data Sheet

Date 02_2020
Supersedes: -

Product Name	Scotch-Brite EXL Unitized Wheel XL-UW																																								
Product Description	3M Scotch-Brite Unitized Wheel is a non-woven abrasive, layered construction for deburring and finishing. Used with portable tools, bench and floor mounted machines on aluminium, steel, brass, titanium, zinc, and other metals																																								
Mineral / Grades Color	<table><thead><tr><th><i>Product I.D.</i></th><th><i>Mineral</i></th><th><i>Grade</i></th><th><i>Density</i></th><th><i>Color</i></th></tr></thead><tbody><tr><td>XL-UW A FIN</td><td>Aluminum Oxide</td><td>Fine</td><td>4,6</td><td>Tan</td></tr><tr><td>XL-UW A MED</td><td>Aluminum Oxide</td><td>Medium</td><td>2,6</td><td>Tan</td></tr><tr><td>XL-UW A CRS</td><td>Aluminum Oxide</td><td>Coarse</td><td>8</td><td>Tan</td></tr><tr><td>XL-UW A XCR</td><td>Aluminum Oxide</td><td>Extra Coarse</td><td>2, 4, 6, 8</td><td>Brown</td></tr><tr><td>XL-UW S VFN</td><td>Silicon Carbide</td><td>Very Fine</td><td>2</td><td>Gray</td></tr><tr><td>XL-UW S FIN</td><td>Silicon Carbide</td><td>Fine</td><td>2, 3, 4, 6</td><td>Gray</td></tr><tr><td>XL-UW S MED</td><td>Silicon Carbide</td><td>Medium</td><td>2</td><td>Gray</td></tr></tbody></table>	<i>Product I.D.</i>	<i>Mineral</i>	<i>Grade</i>	<i>Density</i>	<i>Color</i>	XL-UW A FIN	Aluminum Oxide	Fine	4,6	Tan	XL-UW A MED	Aluminum Oxide	Medium	2,6	Tan	XL-UW A CRS	Aluminum Oxide	Coarse	8	Tan	XL-UW A XCR	Aluminum Oxide	Extra Coarse	2, 4, 6, 8	Brown	XL-UW S VFN	Silicon Carbide	Very Fine	2	Gray	XL-UW S FIN	Silicon Carbide	Fine	2, 3, 4, 6	Gray	XL-UW S MED	Silicon Carbide	Medium	2	Gray
<i>Product I.D.</i>	<i>Mineral</i>	<i>Grade</i>	<i>Density</i>	<i>Color</i>																																					
XL-UW A FIN	Aluminum Oxide	Fine	4,6	Tan																																					
XL-UW A MED	Aluminum Oxide	Medium	2,6	Tan																																					
XL-UW A CRS	Aluminum Oxide	Coarse	8	Tan																																					
XL-UW A XCR	Aluminum Oxide	Extra Coarse	2, 4, 6, 8	Brown																																					
XL-UW S VFN	Silicon Carbide	Very Fine	2	Gray																																					
XL-UW S FIN	Silicon Carbide	Fine	2, 3, 4, 6	Gray																																					
XL-UW S MED	Silicon Carbide	Medium	2	Gray																																					
Fibre/ Bond/	Nylon Phenolic Resin																																								
Thickness/ Dimensions	Various																																								
Identification	All relevant product identification information can be found on the product label or on the box in which the product was received or on the with the product supplied Safety Instruction Leaflet.																																								
Recommended (Ideal) Storage Conditions	Store under "first-in - first-out" base and at recommended conditions (16-26°C/ 35-50% rH). Temperature and humidity beside these conditions should be avoided.																																								
Safety	<p>Please refer to all local safety and industrial standards. Always use appropriate PPE and follow safety precautions as instructed in the associated Product Safety Insert. Product Safety Inserts are included with shipped product and are also available on-line through 3M.com</p> <p>For information please contact your local 3M Office. www.3M.com</p>																																								

For Additional Information	To request additional product information or to arrange for sales assistance, call your local 3M Application Engineering
Important Notice	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law
Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations	

3M is a trademark of the 3M Company

3M Nederland B.V.
Abrasives Systems Division
Molengraaffsingel 29
2629 JD Delft
NEDERLAND

www.3M.nl/abrasives