

Product Description

3M™ Brown Stripper Pad 7100 is a floor maintenance stripping pad made of nylon and polyester fibers in an open-textured, non-woven construction.

Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable resin system that permeates the entire pad.

Unique design and durable construction make these pads the industry standard for consistent performance and long life.

- Designed to strip floor finish from the floor prior to refinishing
- For use on standard, low-speed automatic scrubbers and rotary floor machines (175 - 400 RPM)



Application

This product is used with water-based floor finish stripping solutions to remove old, soiled floor finishes and sealers.

The product is also used to clean heavily soiled hard surface floors such as concrete when used with appropriate cleaning chemicals.

The product is intended for use on standard, low-speed automatic scrubbers and rotary floor machines. For use on finish-coated flooring such as sheet vinyl, vinyl tile, marble, terrazzo, or concrete.

Special Features

Uniform coating throughout every 3M™ floor pad reduces the number of knots and clumps, which eliminates scratching of floors while providing greater consistency and extended pad life.

Pads are reversible and will not be significantly affected by water, detergents, or cleaners normally used for floor maintenance.

Exacting standards for quality mean thickness uniformity from edge to edge and pad to pad is exceptional, resulting in consistent performance without pad wobble or machine vibration.

The precise center-hole placement and roundness of the pads also contribute to the smooth operation, which extends pad life and may help reduce operator fatigue.

Characteristics

The values displayed are the results of illustrative lab test measures and shall not be considered as a commitment from 3M.

Color:	Brown
Printing:	3M
Thickness:	25 mm
Center hole:	Pre-cut at 85 mm
Weight:	1735 g/m ²
Aggressiveness (Schiefer Value):	2.2 g

Directions for Use

- Install under the machine pad holder.
- Apply the stripping solution on a section of the floor to strip.
- Allow to stand for the amount of time following stripping chemical instructions.
- Strip the floor with a floor machine (adding water to keep the floor wet).
- Pick up the dirty solution and rinse the stripped floor twice with clear water.
- Remove the pad and wash it.

Maintenance and Cleaning

- Remove the floor pad from the machine after each use.
- Wash and rinse under tap water or spray water, or keep pads soaked in diluted stripping solution to dissolve residues of dirt. Avoid dirty pads from drying before washing.
- Rinse and hang up to dry.

Note: Do not machine wash!

Packaging

Each carton shall be labeled to identify the contents by product name, size, quantity, and manufacturer. Each pad shall be printed with the manufacturer's name.

Standard Sizes

Circular discs are available in a variety of common sizes.

Storage Conditions and Shelf Life

Storage conditions: +4°C to +40°C, out of sunlight, original container in a clean and dry indoor area.

Health and Safety

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety, and environmental information.

[Follow the link to obtain SDS sheets for 3M products on 3M.com/SDS.](https://www.3m.com/SDS)

[Follow the link to obtain information about substances of very high concern \(SVHC\).](#)

IMPORTANT!

- When using any equipment, always follow the manufacturer's instructions for safe operation.
- This floor pad is for professional or industrial use only.



DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:
DO NOT use this product on any asbestos-containing material.



WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

To reduce the risks associated with environmental contamination:

- Dispose of waste and slurries generated from wet polishing in accordance with all applicable local and government regulations.



CAUTION

The product is intended for wet floor maintenance processes only. DO NOT use this product in any dry application.

Warranty Information

Limited Remedy

This bulletin provides technical information only.

3M recommended product end uses are listed in each 3M product bulletin. End uses not listed in the applicable 3M Product Bulletins are typically not eligible for 3M Warranties. For non-recommended and/or non-warranted end uses or applications, users must test and approve the end uses or applications, assume any associated risks, and acknowledge that 3M has no liability for such end uses or applications. Please contact your 3M representative with any questions about applications, end uses, and warranties.

Limitations of liability

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

3M is a trademark of 3M. All other trademarks are the property of their respective owners.

3M United Kingdom PLC

Commercial Branding and Transportation
Cain Road
Bracknell, RG12 8HT
UK

© 3M 2025. All rights reserved.