



Quick Links

[Facilities Website](#)

[Safety Data Sheets \(SDS\)](#)

Some of these links lead to web-based resources that are not product-specific.

Graphics applied to floor and covered by 4+ layers of acrylic floor finish

- Scrub daily. Use a 3M™ Red Buffer Pad 5100 or Scotch-Brite™ Clean & Shine Pad on an autoscrubber with a neutral cleaner. A mop and bucket with a neutral cleaner can be used in areas not maintained with an autoscrubber.
- High-speed burnish. Use an appropriate burnish pad for the acrylic finish.
- Scrub and recoat. Wet scrub using a Scotch-Brite™ Surface Preparation Pad Plus and water. Apply 2+ coats of acrylic finish.
- Strip and recoat. Remove the current floor graphic during stripping process when possible. Use appropriate floor stripper with stripping pad to remove old finish. Clean floor thoroughly with neutral cleaner. Apply new floor graphic. Coat with 4+ layers of acrylic floor finish.



Graphics applied on top of floor coatings or uncoated floor surface

- Scrub daily. Use a 3M™ Red Buffer Pad 5100 or Scotch-Brite™ Clean & Shine Pad on an autoscrubber with a neutral cleaner. A mop and bucket with a neutral cleaner can be used in areas not maintained with an autoscrubber.
- Do not high-speed burnish. If high-speed burnish is necessary, remove the floor graphic, burnish floor, and apply a new floor graphic.
- Scrub and recoat (acrylic floor finishes). Remove the current floor graphic. Wet scrub using a Scotch-Brite™ Surface Preparation Pad Plus and water. Apply desired number of coats of floor coating. Apply a new floor graphic after floor coating has cured.
- Strip and recoat (acrylic floor finishes). Remove the current floor graphic. Use appropriate floor stripper with stripping pad to remove old finish. Clean floor thoroughly with neutral cleaner. Apply new floor graphic. Coat with 4+ layers of acrylic floor finish.
- Scrub and recoat of surfaces coated with Scotchgard™ Stone Floor Protector or Scotchgard™ Resilient Floor Protector. Remove the current floor graphic. Wet scrub using a Scotch-Brite™ Purple Diamond Pad Plus and water. Apply one or two coats of Protector. Apply a new floor graphic after Protector has cured.
- Re-polish of stone, concrete, or terrazzo. Remove the current floor graphic. Remove floor coating. Use appropriate sequence of diamond abrasives to refine floor. Apply desired sealer, protector, or coating. Apply a new floor graphic.



Health and Safety

CAUTION

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to [3M.com/SDS](https://www.3m.com/SDS), or by mail or in case of an emergency, call 1- 888-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the **Customer Service Department at 1-800-852-9722**.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty

3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.