



# The Tape for Every Task – 3M Electrical Tapes Guide

Still not sure which 3M™ PVC Electrical Tape is right for your application?  
Use this simple chart to compare the options or visit [www.3M.co.uk/electrical](http://www.3M.co.uk/electrical)



Typical Values	3M™ Temflex™ Tape 1300	3M™ Temflex™ Tape 1500	Scotch® Tape 35	Scotch® Super 33+™ Tape	Scotch® Tape Super 88
<b>Best For</b>	Simple Light Tasks	Medium Duty Applications	Medium to Heavy Duty	Medium to Heavy Duty	Heavy Duty
<b>Target Applications</b>	General bundling, marking, and secondary insulation	Temporary and/or non-critical marking, bundling, holding and secondary insulation	Permanent low-voltage primary and secondary insulation	Permanent, low -voltage primary and secondary insulation, cable jacketing and mechanical protection	Permanent low-voltage primary and secondary insulation, cable jacketing, mechanical protection and padding
<b>Application Environment</b>	Normal temperatures and ambient conditions	Moderate temperatures and conditions	Harsh temperatures and moist or corrosive conditions	Extreme temperatures and moist or corrosive conditions	Extreme temperatures and moist, corrosive or rough conditions
<b>Certifications</b>	IEC 60454-3-1-1/F-PVCP/60 and RoHS2015/863/ EU Compliant	VDE Certified, UL 510 Listed, IEC 60454-3-1-5/F-PVCP/90 and RoHS2015/863/ EU Compliant	CSA and VDE Certified, UL 510 Listed, IEC 60454-3-1-6/F-PVCP/90 and RoHS2015/863/ EU Compliant	CSA and VDE Certified, UL 510 Listed, IEC 60454-3-1-7/F-PVCP/90 and RoHS2015/863/ EU Compliant	CSA and VDE Certified, UL 510 Listed, IEC 60454-3-1-7/F-PVCP/90 and RoHS2015/863/ EU Compliant
<b>Operating Temperature<sup>1</sup></b>	0 to 60°C	0 to 90°C	-10 to 105°C	-18 to 105°C	-18 to 105°C
<b>Thickness</b>	0.13mm	0.15mm	0.18mm	0.18mm	0.22mm
<b>Sticking Power</b> (Adhesion to Steel)	1.7 N/10mm	1.8 N/10mm	2.2 N/10mm	3 N/10mm	3 N/10mm
<b>Stretch<sup>2</sup></b> (Elongation)	150%	170%	225%	250%	250%
<b>Strength<sup>2</sup></b> (Backing Strength)	20 N/10mm	20 N/10mm	30 N/10mm	26.3 N/10mm	35 N/10mm
<b>Insulation<sup>2</sup></b> (Dielectric Strength)	38 kV/mm	40 kV/mm	49 kV/mm	45 kV/mm	45 kV/mm
<b>Colour Details<sup>3</sup></b>					

<sup>1</sup> Temperature range may vary by local agency standards.

<sup>2</sup> Based on ASTM D 1000. Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 23°C unless otherwise stated.

<sup>3</sup> Not all colours available globally. Other colours may also be available in your local market. Yellow/Green typical values may vary. See local datasheet for details.