



Technical Data Sheet

Effective: 05/10/2020 Supersedes: N/A

Automotive Aftermarket Division

3M™ Grippy Sanding Cloth

1) Part Numbers

Grippy Sanding Sheets 139 mm x 114 mm) (5.5 inch x 4.5 inch)	
35109	3M™ Grippy Sanding Cloth, P320
35110	3M™ Grippy Sanding Cloth, P400
35111	3M™ Grippy Sanding Cloth, P600
35112	3M™ Grippy Sanding Cloth, P800
35113	3M™ Grippy Sanding Cloth, P1000
35114	3M™ Grippy Sanding Cloth, P1200
35115	3M™ Grippy Sanding Cloth, P1500
35116	3M™ Grippy Sanding Cloth, P2000
Grippy Sanding Block 112 mm x 70 mm x 19 mm (4.4 inch x 2.75 inch x 0.75 inch)	
35123	3M™ Grippy Sanding Block

2) Description and end uses

High performance product designed for use by hand, particularly for hard to reach areas. Product has very good initial and sustained cut for use on clear coats, paint, primer and plastics.

Grippy backing utilises patented technology to provide maximum hold during use. Product can be used wet or dry.

Grade	Applications	Comments
P320	Bumper sanding e-coated new panel sanding	
P400	Final refinement before 2K paint application Plastic bumper sanding e-coated new panel sanding Stone chip sanding – prep for base coat and clear coat application	Not advisable on silvers etc
P600	Final primer sanding before critical base coat application (water-based BC)	
P800	Final primer sanding before critical base coat application Blending	
P1000	Blending	
P1200	Coarse defect removal (orange peel) as part of Paint Rectification Polyurethane Clear coat rectification	
P1500	Defect Removal- Paint Rectification	
P2000	Minor defect removal- Paint Rectification	Minor texture adjustment



Technical Data Sheet

Effective: 05/10/2020 Supersedes: N/A

3) Physical Properties

Backing: Flexible sanding cloth backed abrasive with 3M™ Gripping attachment system using patented microreplication technology.
Mineral: Aluminium Oxide
Bonding: Resin Bond
Colour: Blue abrasive cloth with yellow gripping material
Grades: P320 – P2000 (FEPA)

4) Directions for Use

Universal product can be used wet or dry by hand for a variety of applications.

5) Storage

It is recommended that all Coated Abrasive Products should be stored at constant levels of temperature and humidity within the ranges of 18-22°C, 50-65% RH. They should be kept away from damp (or cold) walls, windows or floors to avoid possible moisture absorption. Equally storage adjacent to heat sources e.g. steam pipes, radiators, hot air ducts, ovens, etc. should be avoided. Product is best stored in original packaging until ready for use. Shelf Life indefinite under these conditions.

6) Safety

Whenever possible, sanding should be carried out in a well-ventilated area and it is strongly recommended that suitable goggles, dust mask and gloves are worn. Pads should not be modified in any way. They should be used only in their original size and shape, as supplied.

3M™ Grippy Sanding Cloth is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.



Technical Data Sheet

Effective: 05/10/2020 Supersedes: N/A

For Additional Health and Safety Information

3M South Africa & Sub-Saharan Africa, 146A Kelvin Drive, Woodmead, Sandton, South Africa, Tel: (0861) 225536
3M (East) AG Representation Office Tirane, Rruga Sami Frasherri, Pallati i Ri Perxhola Kati 2 Ap2, 1000 Albania
3M Arabia, LLC, Building 24-25 3M Saudi Arabia Zone C, Business Gate, Airport Road, Riyadh, Saudi Arabia
3M Bulgaria, Mladost 4, Business Park, bl.4, 2nd floor, Sofia 1766, Bulgaria
3M Česko, spol. s r.o., V Parku 2343/24, 148 00 - Praha 4, Czech Republic
3M (East) AG, Branch office Croatia, Avenija Većeslava Holjevca 40, 10 000 Zagreb, Croatia, Tel: +385 1 2499750, www.3m.com.hr
3M Egypt, Finance Center , New Cairo , Plot 140 , Banking Sector , 5th settlement , Cairo , Egypt
3M Hellas MEPE, Automotive Aftermarket Division, 20 Kifisias Avenue, 151 25 Marousi, Greece, Phone: +30 210 68 85 300, innovation.gr@mmm.com, www.3M.gr
3M Hungária Kft, Neumann János u. 1/E, 1117 Budapest, Hungary
3M Israel, 91 Medinat Hayehudim St., Herzliya, Israel
3M Kenya Ltd, Victoria Towers, 3rd Floor, Kilimanjaro Av, Upperhill, Kenya
3M Gulf Limited, Ein El Mreisseh, Saint Charles City Center, 4th. Floor, P.O.Box: 11-5025, Riad el Solh, Beirut 1107 2180 Lebanon
3M Minnesota Mining & Manufacturing Nigeria Limited, No 2 Sheraton Opebi Link Road, Ikeja, Lagos Nigeria
3M Pakistan, Islamic Chamber of Commerce Building, ST-2/A, Block 9, KDA Scheme 5, Clifton, Karachi, Pakistan
3M Poland, Al. Katowicka 117, Kajetany, 05-830 Nadarzyn, Poland, Telefon: +48 22 739 60 00, www.3m.pl/kontakt
3M Gulf (Representation Office), Suhaim Bin Hamad St., Al Mana Towers Tower B, 2nd Floor, Office No.4, Doha Qatar, P.O.Box 14685
3M Romania, 12 Menuetului St., Bucharest Business Park, Building D, District 1 013713 Bucharest, Romania
3M (East) AG, Representation Office Serbia, Airport City, Omladinskih brigada 90B, 11070 Belgrade, Serbia, Tel: +381 11 2209 400, www.3m.co.rs/3M/sr_RS/3m-south-east-europe/
3M Slovensko s.r.o., Polus Tower 2, Vajnorská 100/B, 83104 Bratislava
3M (East) AG, Branch office Slovenia, Cesta v Gorice 8, 1000, Ljubljana, Slovenia, Tel: +386 1 2003 630, www.3m.com/3M/sl_SI/3m-south-east-europe/
3M Sanayi ve Ticaret As, Barbaros Mah., Mor Sümbül Sok., No:7/3F, 27-51, Nidakule Ataşehir Güney, 34746 Ataşehir, İstanbul, Turkey
3M Gulf Limited, Dubai Internet City, Building No. 11, 3rd Floor, U.A.E

3M is the trademark of 3M Company, © 3M 2021, All rights reserved.