

3M Science.
Applied to Life.™



3M™ Silicone Spray Low VOC and 3M™ 5-Way Penetrant

Simplify your everyday,
hands-on industrial jobs.

3M™ Silicone Spray Low VOC is a reliable, fast-drying lubricant that can be used in a wide variety of industrial applications. This long-lasting product can eliminate rubber squeaks and is non-staining to keep your work surfaces clean.

Our **3M™ 5-Way Penetrant** attacks the corrosion that prevents the movement of commonplace parts, such as rusty levers, nuts or bolts. We designed this versatile, silicone-free chemical to spray evenly, spreading a thin, even film that penetrates the toughest barriers.



Why Choose 3M™ Silicone Spray Low VOC 60% and 3M™ 5-Way Penetrant?

3M™ Silicone Spray Low VOC 60%

- ▶ Reliable lubricant can be used in a wide variety of applications
- ▶ Fast drying to maintain productivity
- ▶ Long lasting and non-staining to keep work surfaces clean



3M™ 5-Way Penetrant

- ▶ Helps free rusted and frozen bolts, nuts and more
- ▶ Can act as a tapping lubricant for stainless steel and aluminum
- ▶ Displaces moisture and “dries out” electronics
- ▶ Light duty lubricant works well with delicate precision instruments
- ▶ Inhibits corrosion during storage

Product	3M ID	Legacy ID	UPC	Size	Key Characteristics
3M™ Silicone Spray Low VOC 60% 	7000121413	62469949309	00051111077320	13.4 oz	Silicone base release agent for industrial lubrication applications. It is a low VOC product designed to meet CARB and OTC VOC product consumer regulations without sacrificing product performance.
3M™ 5-Way Penetrant	7000028601	62497849307	00021200213052	16.8 oz	Attacks the corrosion that prevents the movement of commonplace parts, such as rusty cranks, levers and handles, as well as nuts and bolts that have seized. Designed to spray evenly, spreading a thin, even film that penetrates the toughest barriers.



3M Industrial Adhesives & Tapes
3M Center, Bldg 225-3S-06
St. Paul, MN 55144-1000 USA

Phone 1-800-362-3550
Web 3M.com/sprayadhesives

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M is a trademark of 3M Company. All other trademarks are property of their respective owners. © 3M 2021. All rights reserved.