

# Build smarter, even in the toughest conditions.

3M<sup>™</sup> Air and Vapour Barrier 3015NP

3M<sup>™</sup> Air and Vapour Barrier 3015NP provides building protection that installs faster<sup>\*</sup> under extreme conditions without sacrificing performance. 3M acrylic adhesive technology allows for primer-free application from lightweight rolls that saves you up to 40% on installation time compared to traditional barriers that require a primer.









Highly compatible with other materials

### Let's Build Smarter.



#### **Benefits**

- Increased opacity provides a clean look and visibility of screw heads to minimize missing the stud
- Compatible with most sealants and building materials
- Meets AAMA 711-13 Voluntary Specification for Self Adhering Flashing Use for Installation of Exterior Wall Fenestration Products
- ABAA Evaluated

#### abaa •\*\*

# Up to 40% time savings.\*

No primer required. Aggressive, high-tack pressure-sensitive acrylic adhesive technology eliminates the time and materials usually needed for applying air barriers.

# 3M acrylic adhesive increases compatibility.

- Compatible with a wide range of common sealants, including synthetic rubber, butyl, polyurethane, silicone and silane-terminated hybrid sealants
- Passes NFPA 285 as part of various exterior wall constructions
- Sticks well to concrete, concrete block, anodized aluminum, galvanized metal, plywood, extruded polystyrene and most exterior gypsum sheathing

## Extended temperature range increases production.

- Productivity in all conditions. Application temperatures from -18° to 66°C (0° to 150°F)
- Service temperature range from -40° to 116°C (-40° to 240°F)

#### \*As compared to traditional primer applied air barriers. Independent Observation and White Paper written by Lee Durston, Director of Building Science and Dani Ittner, Building Envelope Architect, BCRA Inc., September 2012.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs). 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, warranty, contract, negligence, or strict liability.

3M and 3M Science. Applied to Life. are trademarks of 3M. Used under license in Canada. © 2021, 3M. All rights reserved. 2104-20280 E



3M Industrial Adhesives and Tapes Division 3M Canada P.O. Box 5757 London, ON N6A 4T1

1-800-364-3577 3M.ca/AirBarrier

## Let's Build Smarter.