### **Product Benefits**

- Helps reduce interior damage due to fading
- Helps to reduce eyestrain
- Up to 99% UV Protection

# **Product Performance & Technical Data**

Auto 75*	Film	Visible Light Transmittance	Visible Light Reflectance Exterior	Visible Light Reflectance Interior	UV Block	Total Solar Energy Rejected	Glare Reduction	Infrared Rejection****	Infrared Energy Rejection****
	Auto 75 Glass	73%	7%	7%	67%	42%	NA	NA	NA
	FXST 5	4%	4%	4%	99%	61%	95%	8%	54%
	FXST 20	20%	4%	5%	99%	57%	74%	8%	53%
	FXST 35	28%	4%	5%	99%	54%	63%	7%	54%
	FXST 40	35%	5%	5%	99%	53%	54%	7%	53%
	FXST 50	45%	5%	5%	99%	50%	40%	7%	53%
	FXST 70	59%	6%	7%	99%	46%	21%	8%	53%

6mm Clear**	Film	Visible Light Transmittance	Visible Light Reflectance Exterior	Visible Light Reflectance Interior	UV Block	Total Solar Energy Rejected	Glare Reduction	Infrared Rejection****	Infrared Energy Rejection****
	Clear Glass	89%	9%	8%	34%	19%	NA	NA	NA
	FXST 5	4%	5%	4%	99%	46%	95%	8%	24%
	FXST 20	23%	5%	5%	99%	40%	74%	8%	23%
	FXST 35	33%	5%	5%	99%	37%	63%	7%	24%
	FXST 40	51%	5%	5%	99%	35%	53%	7%	24%
	FXST 50	54%	6%	6%	99%	31%	39%	7%	23%
	FXST 70	70%	7%	7%	99%	28%	21%	8%	23%

<sup>\*</sup> Data should be used as a reference tool for net VLT on ¼" (6mm) thick, automotive green glass of 73% VLT, and testing is in accordance to ANSI/NFRC 200 Procedure.

## **Commercial Solutions Division**

3M Center, Building 220-12E-04 St. Paul, MN 55144 3M.com/windowfilm

© 3M 2021. All rights reserved. 3M is a trademark of 3M. Used under license in Canada. All other trademarks are property of their respective owners. Revision A, May 2021. Please recycle.



<sup>\*\*</sup> Data is comparable to current auto industry method using a clear 89% VLT glass, and testing is in accordance to ANSI/NFRC 200 Procedure.

<sup>\*\*\*</sup>Will not interfere with cell phones, GPS systems or satellite radio.

<sup>\*\*\*\*</sup>IRR - IR Rejected over 900 - 1,000 nm. Film with liner measurement

<sup>\*\*\*\*\*</sup>IRER – The percent of solar infrared energy rejection over the wavelength range from 780 – 2,500 nm. IRER takes into account the transmitted and absorbed IR energy that will be reradiated into a car. Film is applied to glass

**FXST Series** 

### AIS

View the Article Information Sheet (AIS), document # 20-1344-9 for 3M FXST Series at 3M.com/SDS.

## **Technical Information**

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third-party intellectual property rights is granted or implied with this information. If you have questions about this Product, contact the Customer Service Department at 1-866-499-8857.

### **Product Selection and Use**

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

# Warranty, Limited Remedy and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

# Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

## **Commercial Solutions Division**

3M Center, Building 220-12E-04 St. Paul, MN 55144 3M.com/windowfilm

© 3M 2021. All rights reserved. 3M is a trademark of 3M. Used under license in Canada. All other trademarks are property of their respective owners. Revision A, May 2021. Please recycle.

