



**V.A.C.®**  
Therapy






# The only 3M™ V.A.C.® Therapy Unit able to treat up to 4 open wounds in one device\*

The 3M™ V.A.C.® Rx4 Therapy System was designed with military combat and complex trauma environments in mind.



3M™ V.A.C.® Rx4 Therapy System with 3M™ SensaT.R.A.C.™ Technology

	Unique Features	Product Benefits
	<p>Each channel is numbered and has its own:</p> <ul style="list-style-type: none"> <li>• User interface (pressure, therapy mode, intensity, display)</li> <li>• Pump, fluid path, and canister</li> </ul>	<p><b>Clearly numbered channels put you in control so you can treat based on the unique needs of each wound</b></p>
	<p>Simple user interface</p> <ul style="list-style-type: none"> <li>• Few as 5 button touches needed to activate all 4 channels</li> <li>• Under 30 seconds to start up system</li> <li>• Recessed full-color LCD screen</li> </ul>	<p><b>Intuitive design means a more efficient workflow for you and the staff</b></p>
	<p>Compatibility with existing accessories</p> <ul style="list-style-type: none"> <li>• 500ml or 1000ml V.A.C. Canisters</li> <li>• 3M™ V.A.C.® Granufoam™ Dressing™, 3M™ V.A.C. Whitefoam™ Dressing, 3M™ V.A.C.® Granufoam Silver™ Dressing and 3M™ Prevena™ Incision Dressing</li> </ul>	<p><b>Peace of mind that 3M™ V.A.C.® Rx4 Therapy System works with many of your preferred V.A.C.® Therapy dressing kits and canisters</b></p>

\*In a single patient.

# 3M™ V.A.C.® Rx4 Therapy System: The power to multi-task wound care

- Utilizes proprietary 3M™ SensaT.R.A.C.™ Technology in all 4 channels to maintain and adjust delivery of prescribed pressure at each wound site
- The 3M™ V.A.C.® Rx4 Therapy System efficiently treats a single patient with up to 4 independent wounds
- Easy-to-use interface for military combat and trauma care settings
- Compatible with many of your preferred V.A.C.® Therapy dressings and canisters.

## Specifications

Dimensions (without canisters)	28cm x 27cm x 36cm
Weight (without canisters)	about 7.3kg
Pressure	-50 to -200mmHg (-6.7 to -26.7kPa)
Therapy delivery modes	Continuous, intermittent
Canister volume	500ml or 1000ml

## Electrical

Battery run life	approx. 8 hours, depending on settings
Battery charge time	approx. 12 hours from a fully-discharged state
External power supply input	100-240VAC, 2A, 50-60Hz
External power supply output	15V, 10A
Patient and enclosure leakage current	<100 Microamps

## Environmental Conditions

### Storage Conditions

Temperature range	-18°C to 60°C / 0°F to 140°F
Relative humidity range	15-90% non-condensing

### Operating Conditions

Temperature range	14°C to 35°C / 57°F to 95°F
Relative humidity range	20 - 80% non-condensing
Atmospheric pressure	1060hpa to 700hpa
Altitude range	up to 3000m / 9842 ft

**For more information please contact your local representative or call 800-275-4524.**

**Note:** Specific indications, contraindications, warnings, precautions, and safety information exist for these products and therapies. Please consult a physician and product instructions for use prior to application. Rx only.



**3M Company**  
2510 Conway Ave  
St. Paul, MN 55144 USA

Phone 1-800-275-4524 (NPWT products)  
1-800-228-3957  
Web 3M.com/medical

© 2021 3M. All rights reserved. 3M and the other marks shown are marks and/or registered marks. Unauthorized use prohibited.  
70-2013-1054-0 PRA-PM-US-03204 (06/21)