

3M

ScotchPad™

Pouch Tape Pads

830 • 832 • 830CP • 832CP

Technical Data

November 2017

Product Description 3M™ ScotchPad™ Pouch Tape Pads are pre-cut pressure-sensitive tapes with a sticky border and a printed, non-tacky center section that comes either as a standard or custom printed pouch which is clear and becomes a “see-through” window. Each piece of tape is coupled with a strip of liner material for easy handling and application without the need of a dispenser. The product provides a quick, simple, and secure method of attaching and protecting packing lists and other documents on a wide range of shipping containers. With the liner left in place, the product may be used as an open-ended pouch, allowing work tickets, inventory lists, and other shipping documents to be inserted or removed as necessary.

Construction	Backing:	3M™ Scotchpro™ polypropylene	
	Film Adhesive:	Pressure-sensitive rubber resin	
	Colors		
	Standard Pouch Pad:	(830/832)	Transparent film with orange/white message border.
	Custom-Printed Pouch Pad:	(830CP/832CP)	Transparent film with choice of two (2) colors and clear detackifying varnished center.
Dimensions			
	Tape Sheet:	ScotchPad 830 – approximately 5 in. x 6 in. ScotchPad 832 – approximately 6 in. x 10 in.	
	Tack Free Area:	ScotchPad 830 – approximately 4 in. x 4 ⁷ / ₈ in. ScotchPad 832 – approximately 5 in. x 8 ³ / ₄ in.	
	Window (Readable Area):	ScotchPad 830 – approximately 3 ¹ / ₈ in. x 4 ¹ / ₂ in. ScotchPad 832 – approximately 4 in. x 7 ⁷ / ₈ in.	

Typical Physical Properties Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	50 oz./in. width (55 N/100 mm width)	D-3330
Tensile Strength:		
Crosswise:	30 lbs./in. width (525 N/100 mm width)	D-3759
Lengthwise:	60 lbs./in. width (1050 N/100 mm width)	D-3759
Total Thickness:	2.5 mil (0.066 mm)	D-3652
Elongation at Break:	160%	D-3759
Shear Holding to Fiberboard:	8000+ minutes	D-3654

Features	• Liner tab.	• Easy removal of liner.
	• Pre-cut individual sheets.	• Portable, lightweight.
	• Strong and abrasion-resistant.	• Space-saving.
	• Easy removal of single sheets.	• Standard and custom messages available.
	• Aggressive adhesive provides excellent adhesion to various surfaces.	• Consistent dimensions.

3M™ ScotchPad™ Pouch Tape Pads

830 • 832 • 830CP • 832CP

Features (*continued*)

- Exact replication of sheet size and border print.
- Helps prevent labels, invoices, and such from being scuffed off.
- Easy to read label.
- Holds securely to most cartons and containers; keeps packing list or label on package for safe delivery.
- Fast application; saves time.
- Easy to carry in pad form.
- Calls attention to and prevents disposal of documents.
- Excellent bar code protection.
- Customer's name, address, and logo or telephone and advertisement may be printed on the custom pouch tape pads.

Available Packaging

	Sheets/Pad	Pad/Carton	Cartons/Case	Pads/Case	Application/Case
3M™ ScotchPad™ 830	25	40	5	200	5000
3M™ ScotchPad™ 832	25	40	4	160	4000

Storage Conditions

It is recommended that 3M™ ScotchPad™ Pouch Tape Pads be stored below 85°F (29°C).

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 225-3S-06, St. Paul, MN 55144-1000. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.