

# **3M<sup>™</sup> Acrylic Foam Tape 5935**


# **Technical Data Sheet**



# **Description**

3M™ Acrylic Foam Tape 5935 is a 0.4 mm thick, medium-density, gray acrylic foam tape constructed with two different adhesives. The heat-activated adhesive forms an immediate, consistent and durable bond to most EPDM formulations and Santoprene® materials. The pressure-sensitive adhesive is characterized by high adhesion and holding strength to many surfaces, including automotive paints and metals. This tape has good conformability and is used to attach weatherstrip and/or gasket seals for automotive and industrial applications. It is recommended for applications where the vehicle taping surface is smooth and a thin tape is necessary.

### **Product Construction**




## **Physical Properties**

Values shown are typical values not to be used for specification purposes.


5935	
Thickness Range (excluding liner)	0.40 mm ±0.05 mm (0.016 inch ±0.002 inch)
Density Range (excluding liner)	737 kg/m³ ± 80 kg/m³ (46 lb/ft³ ± 5 lb/ft³)
Tabbing	3M™ Tabbing Tape 5400

# **Performance Properties**

## 90° Peel Adhesion



Typical performance of  $3M^{\mbox{\tiny M}}$  Acrylic Foam Tape 5935 is shown below. Peel values depend on the composition and cross-section of a particular weatherstrip. These values are for reference only.



#### **Shelf Life**

36 months from date of manufacture when stored at 4°C–38°C (40°F–100°F) and 0–95% relative humidity (RH). The optimum storage conditions are 22°C (72°F) and 50% relative humidity.

## **Regulatory Information**

IMDS# 8996612. This is a published material entry on <a href="www.mdsystem.com">www.mdsystem.com</a>.

#### **Contact Information**

The information provided in this technical document is intended as a guide for this product. For more information or help in selecting a 3M product for an application, please contact your 3M application engineer or call product application support at 1-800-328-1684.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information. Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Automotive and Aerospace Solutions Division 3M Center St. Paul, MN 55144-1000 1-800-328-1684 3M.com/autosolutions