

3M[™] Double Coated Tapes GPT-020 / GPT-020F is the ideal general purpose industrial thin bond tape for a wide range of applications and substrates.

Expect performance. Spec 3M.

Your go-to tape for greater design possibilities.

- Solventless adhesive technology
- High initial tack
- High thermal and humidity resistance
- High peel performance on a wide range of surfaces
- Superior high-temperature shear performance
- Adhesion to a wide variety of substrates ranging from metals to some plastics
- Easy handling and converting due to both paper and filmic liner delivery
- Perfect for a variety of markets, including consumer appliances, industrial machinery, transportation, consumer electronics

Bonds to many high surface energy substrates and some low surface energy substrates, including:

- Stainless steel
- ► HDPE
- ► ABS
- ► Acrylic
- ► PP
- Polycarbonate
- Aluminium
- ► Glass

Creating designs in applications.

Rising to the challenge in many markets including consumer appliances, industrial machinery, transportation, signage, general industrial and consumer electronics.



- ► POP/POS displays
- Light boxes
- Indoor/outdoor signs
- Paper bonding and packaging

- Metal fabrication
- Splicing and bonding
- Sports equipment
- Home decoration
- Trim attachment in appliance
- Mounting of plastic parts
- Mounting in electronics
- Furniture trim attachment

The next generation of thin bonding.



3M[™] Double Coated Tape GPT-020 / GPT-020F

	GPT-020	GPT-020F
Adhesive	Solventless acrylic	Solventless acrylic
Carrier type (thickness)	PET 12 micron	PET 12 micron
Liner type (thickness)	White PCK 100 micron	White PP 100 micron
Total tape thickness without liner	200 micron	200 micron
Short term temp. performance	190°C	190°C
Long term temp. performance	90°C	90°C
Colour	Transparent	Transparent
Roll type	Planetary rolls	Planetary and level wound rolls

For more information, please visit: www.3M.co.uk/tapes

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Industrial Adhesives and Tapes Division



Contact Product Details Where to buy



