

**3M** Science.  
Applied to Life.™



## Tackle the toughest jobs in the business.

When safety is most important, it's critical your firestop sealant is easy to install and meets the intent of the building code. We know you're facing firestop challenges and project complexities every day, and we're committed to bringing you products that make your job easier and more effective while also meeting today's environmental challenges. Use our 3M™ Fire Barrier Sealant CP 25WB+ for restoring

the fire-rated integrity of walls, floors and ceilings by sealing through-penetrations to control the spread of fire, smoke and noxious gases. Our ready-to-use, high-performance sealant with intumescent latex technology secures a lasting seal for up to 4 hours. Our sealant meets the intent of LEED VOC guidelines and is approved for use in more than 600 combined UL and Intertek listings.



## Build smarter with 3M™ Fire Barrier Sealant CP 25WB+

Effective and easy to install, 3M™ Fire Barrier Sealant CP 25WB+ is part of our 3M Fire Barrier portfolio with affordable, long-lasting solutions for a variety of commercial, industrial and residential applications.

Let's Build Smarter.

# Applications

- HVAC Ducts and Vents
- Metal Pipe
- Plastic Pipe\*
- Blank Openings
- Cable Trays
- Insulated Pipe
- Pipe and Cable Through-Penetrations
- Busways
- Construction Joints
- Combos
- Concrete Floors
- Static Construction Joints



# Features and Benefits

- Versatile for use in multiple firestopping applications
- Listed systems for ratings up to 4 hours
- Water-based and paintable
- More than 600 UL and Intertek listings
- Easy to identify red color
- Easy to apply
- Meets the intent of LEED VOC guidelines\*\*
- Minimizes noise transfer — STC-Rating of 54 when tested with STC 54-rated wall assembly

# Specifications

3M™ Fire Barrier Sealant CP 25WB+ shall be a one-component, ready-to-use, gun-grade, latex-based intumescent firestop sealant capable of expanding a minimum of 3 times its dried volume when exposed to temperatures above 1000°F (538°C). The material shall be thixotropic and shall be applicable to overhead, vertical and horizontal firestops. The sealant shall be listed by independent test agencies such as UL, Intertek or FM. 3M™ Fire Barrier Sealant CP 25WB+ shall be tested up to 4 hours in accordance with the criteria of ASTM E814 (UL 1479) Standard Test Method for Fire Tests of Penetration Firestop Systems, ASTM E1966 (UL 2079) Standard Test Method for Fire Resistive Joint Systems and CAN/ULC S115 Standard Method of Fire Tests of Firestop Systems. 3M™ Fire Barrier Sealant CP 25WB+ meets the requirements of the IBC, IRC, IFC, IPC, IMC, NFPA 5000, NEC (NFPA 70) and NFPA 101.



Product	Size	UPC	Qty/Cs	Material ID
3M™ Fire Barrier Sealant CP 25WB+	10.1 fl. oz. Cartridge	98-0400-5456-5	12	700006383
	27 fl. oz. Cartridge	98-0400-5382-3	6	7000059394
	20 fl. oz. Sausage	98-0400-5383-1	10	7000145569
	2 Gallon Pail	98-0400-5380-7	1	7100006311
	5 Gallon Pail	98-0400-5381-5	1	700006379

Learn how 3M's advanced adhesive technologies can help you build smarter. Visit [3M.com/firebarrier](http://3M.com/firebarrier) or contact your 3M representative.



**3M Industrial Adhesives and Tapes Division**  
3M Center, Building 220-5E-06  
St. Paul, MN 55144 USA

Phone 1-800-328-1687  
Web [3M.com/firebarrier](http://3M.com/firebarrier)

\*Check UL directory. Not approved for use with CPVC pipes. Contact the CPVC pipe manufacturer for additional information.

\*\*Helps reduce the quality of indoor air contaminants that may be odorous, irritating and harmful to the comfort and well-being of the installers and occupants. <250 g/L VOC contents (less H2O and exempt solvents).

**Product Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

**Warranty, Limited Remedy and Disclaimer:** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M, 3M Science Applied to Life and Interam are trademarks of 3M Company. Noveon, Intertek, UL and FM are trademarks of their respective owners. © 3M 2022. All rights reserved. Printed in USA.