



		atic	
Sn	ΗС	atic	ne
Uμ		auc	ЛIЭ

Air Consumption: 370 SLPM [13 SCFM]

Recommended Air Inlet Pressure: 1.38 Bar [20 psi] Maximum Operating Temperature: 50 °C [122 °F] Maximum Operating Overpressure: 10 Bar [145 psi]

**Weight**: 238 g [13.3 oz] **Air Inlet:** 1/4 BSP/NPS

Nozzle Orifice Sizes: 0.9, 1.2, 1.3, 1.4, 1.6, 1.8, 2.0

Spray Guns and Systems				
Product	Part No.			
3M™ Performance Spray Gun System				
(1 spray gun, 1 air control valve, 1 locking collar, 15 gravity atomizing heads, 1 3M™ PPS™ Series 2.0 mixing cup, 5 lids and liners, 3 sealing plugs)	26778			
3M™ Performance Spray Gun (Spray gun and air control valve)	26832			

Replacement Parts and Accessories				
Product	Part No.			
3M™ Performance Spray Gun Locking Collar	26835			
3M™ Performance Spray Gun Rebuild Kit	26840			
3M™ Performance Spray Gun Needle	26838			
3M™ Performance Spray Gun O-Ring Kit	26841			
3M™ Performance Spray Gun H/O Conversion Pack	26837			

HVLP Atomizing Head Refill Kits					
Color	Size	Quantity	Part No.		
White	0.9	5	26709		
Blue	1.2	5	26712		
Green	1.3	5	26713		
Orange	1.4	5	26714		
Purple	1.6	5	26716		
Clear	1.8	5	26718		
Red	2.0	5	26720		
Variety Kit	6 sizes (1.2, 1.3, 1.4, 1.6, 1.8, 2.0)	6	26730		



## Guaranteed Trial Order.

If you aren't 100% satisfied, return to 3M for a full refund within 45 days of purchase. No questions asked.

Contact your local 3M representative to get started.



Automotive Aftermarket Division 3M Center Building 223-06S-07 St. Paul, MN 55144-1000 1-877-666-2277

For more information, visit us at 3M.com/spraygun

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for proper evaluation (including, but not limited to, fitness for purpose and suitability of application), selection, and use of 3M products. Safety products should always be selected and used in accordance with all applicable regulations and standards (e.g., OSHA, ANSI, and others), after conducting a proper hazard assessment. Failure to properly evaluate, select, and use a 3M product may result in injury, sickness, death, and/or harm to property. Dispose of used atomizing heads, residual paint/coatings, used containers/materials, and PPS in accordance with local regulations.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M and PPS are trademarks of 3M Company. All other trademarks are property of their respective owners. Please recycle. Printed in USA. © 3M 2022. All rights reserved. 60-4405-0122-3