
3M[™] Trizact[™] Backer Pad

Technical Data Sheet Revision A, March 2022



Product Description

The 3M[™] Trizact[™] Backer Pad is a low-speed (175-600 RPM) pad consisting of a foam center with loop material on both sides. It is designed as an improved backer for 3M[™] Trizact[™] Diamond TZ Pads compared to traditional floor pads.

Special Features

- Loop material firmly holds the 3M[™] Trizact[™] Diamond TZ Pads for extended periods of time through multiple use cycles.
- Compressible foam designed to help conform to low spots or uneven floors
- Usable on both sides
- Allows for easy attachment of the 3M[™] Trizact[™] pads and firmly holds the pads in place.
- Does not clog or require frequent cleaning like floor pads
- Long life; one 3M™ Trizact™ Backer Pad replaces multiple floor pads.

Applications

This product is used in conjunction with 3M[™] Trizact[™] Diamond TZ Pads under an auto scrubber or other standard low speed (175-600 RPM) floor cleaning equipment using water or a neutral cleaner.

It is suitable for use on stone floors such as marble, terrazzo, limestone, travertine, and concrete.

Packaging and Marking

Each carton is labeled to identify the contents by product name, size, quantity, and manufacturer.

Standard Sizes

Circular discs are available in a variety of common sizes. Pads are approximately 0.5 in. thick.

Quick Links

Facilities Website Safety Data Sheets (SDS) Some of these links lead to web-based resources that are not product-specific

Pad Use and Cleaning

For full 3M[™] Trizact[™] Diamond TZ Pad use instructions, please see the <u>3M[™] Trizact[™] Diamond TZ Abrasive Pads & Strips Technical</u> <u>Data Sheet</u>. Use the 3M[™] Trizact[™] Backer Pad in place of the 3M[™] Red Buffer Pad 5100 where instructed.

Installation

Use four 3M[™] Trizact[™] Diamond TZ Pads arranged in the 12 o'clock, 3 o'clock, 6 o'clock, and 9 o'clock positions when using the pads with an autoscrubber or low-speed floor rotary machine with a diameter of 16 in. or more. Use three pads arranged at the 12 o'clock, 4 o'clock, and 8 o'clock positions when using a machine with a diameter of 15 in. or less. See Figure 1.




Figure 1.

Pads may be rinsed with water and hung to dry to remove soil and debris as needed.

Storage

Store indoors in original packaging and under normal climate controlled facility conditions.

Product Characteristics

3M™ Trizact™ Backer Pad	
Construction	Double sided polyurethane foam with loop material
O.D. Dimension	Designated Size ± 1/16 in.
Thickness	Approx. 0.5 in.





DANGER

Indicates a hazardous situation which, if not avoided, will result in serious injury or death.



WARNING

Indicates a hazardous situation which, if not avoided, could result in serious injury or death



DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:

•DO NOT use this product on any asbestos-containing material.

WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:

•Ensure this product is used in the recommended applications with the suggested equipment.

•Do not allow this product to be used by untrained operators.

•Always follow standard safety practices, including wearing appropriate protective apparel, including eye protection, while using this product.

Health and Safety



⚠ CAUTION

When handling any chemical products, read the manufacturers' container labels and the safety data sheets (SDS) for important health, safety, and environmental information. To obtain SDS for 3M products go to <u>3M.com/SDS</u>. To request SDS by mail, or in case of an urgent situation, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturer's instructions for safe operation.

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and

Commercial Solutions St. Paul, MN 55144

© 3M 2022. All rights reserved. 3M, Trizact, and Scotch-Brite are the trademark of 3M. Used under license in Canada. All other trademarks are property of their respective owners. Revision A, March 2022 Please recycle.

apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information. If you have questions about this Product, contact the Customer Service Department at 1-800-626-8578

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment, reviewing all applicable regulations and standards, and reviewing the product label and use instructions. Failure to properly evaluate, select, and use a 3M product in accordance with instructions or to meet all applicable safety regulations may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE. OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



1-800-626-8578 3M.com/Facility