

Product Description

The Scotch-Brite™ Red Floor Pad is a premium-quality floor maintenance pad. It is made of high-quality synthetic fiber, in an open-textured non-woven construction. Polishing particles are dispersed throughout the thickness and bonded with a durable adhesive. Each floor pad has a pre-cut center hole.



Applications

The Scotch-Brite™ Red Floor Pad should be used for routine spray cleaning with low-speed floor machines (150 - 400 RPM). It will clean and increase the shine on most surfaces. The Scotch-Brite™ Red floor pad can also be used wet for routine cleaning under a scrubber dryer.

Features and Benefits

- Designed for cleaning and spray cleaning operations
- Open web construction to collect soil from floors
- Fine fiber mix for effective removal of marks and fast polishing action on floors
- Flexible pad for easier washing after use
- Consistent performance
- Durable pad at work when cleaned carefully after use
- Limited removal of floor finish

Standard Size

Circular discs are available in a variety of common sizes.

Packaging and Marking

Each carton shall be labeled to identify the contents by product name, size, quantity, and manufacturer. Each pad shall be printed with the black “Scotch-Brite™” logo

Characteristics

The values displayed are the results of illustrative lab test measures and shall not be considered as a commitment from 3M.

Characteristics	Value
Fiber type	Polyester
Weight	1420 g/m ²
Outer diameter dimensions	Designated Size ± 1.6 mm
Thickness	Approximately 28 mm
Aggressiveness	Schiefer value = 0.1 g
Color	Red
Packaging Recycle Content	50 – 100% recycled content

Directions for Use

Spray Cleaning

1. Install a clean floor pad under the machine pad holder.
2. Dust mop the entire floor area if necessary.
3. Spray cleaning chemical moderately on a section of the floor.
4. Clean and buff the floor with 4 to 6 passes.
5. Proceed to the next section of the floor.
6. Dust mop the entire floor area if necessary.

Remove and wash after use.

7. Proceed to the next section of the floor.
8. Dust mop the entire floor area if necessary.

Remove and wash after use.

Directions for Use

Cleaning under a scrubber-dryer

1. Install a clean floor pad under the machine pad holder.
2. Clean the floor on a regular basis with 1 or 2 passes.

Remove and wash after use.

Maintenance of the Pad

1. Remove the disc from the machine after each use.
2. Wash and rinse under tap water or keep pads soaked in detergent solution before re-use. Avoid dirty pads from drying before washing.
3. Rinse and hang up to dry.

Note: Washing 3M™ floor pads in the washing machine is possible at a maximum of 40°C, note that it may shrink about 20 mm after the first washing cycle.

Performance Advantages

Durability: about 20,000 sqm under auto scrubbing machines, when properly maintained.

Storage

Storage conditions: +4°C to +40°C, out of sunlight, original container in a clean and dry indoor area.

Health and Safety

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety, and environmental information.

[Follow the link to obtain SDS sheets for 3M products on 3M.com/SDS.](https://www.3m.com/SDS)

[Follow the link to obtain information about substances of very high concern \(SVHC\).](#)

IMPORTANT!

- When using any equipment, always follow the manufacturer's instructions for safe operation.
- This floor pad is for professional or industrial use only.



DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:

DO NOT use this product on any asbestos-containing material.



WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

To reduce the risks associated with environmental contamination:

- Dispose of waste and slurries generated from wet polishing in accordance with all applicable local and government regulations.

Warranty Information

Limited Remedy

This bulletin provides technical information only.

3M recommended product end uses are listed in each 3M product bulletin. End uses not listed in the applicable 3M Product Bulletins are typically not eligible for 3M Warranties. For non-recommended and/or non-warranted end uses or applications, users must test and approve the end uses or applications, assume any associated risks, and acknowledge that 3M has no liability for such end uses or applications. Please contact your 3M representative with any questions about applications, end uses, and warranties.

Limitations of liability

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

3M and Scotch-Brite are trademarks of 3M. All other trademarks are the property of their respective owners.

3M United Kingdom PLC

Commercial Branding and Transportation
Cain Road
Bracknell, RG12 8HT
UK

© 3M 2025. All rights reserved.