

## 3M™ PELTOR™ ComTac™ VII Headsets



### Technical Specifications

**Speech Microphone Type:** Dynamic (MT71) waterproof (IP68), 6m/30min

#### Power/Electrical Characteristics:

- Battery Type: 2x AAA
- Environmental listening: Approximately 50 hours
- Environmental & NIB: Approximately 30 hours

#### NIB "Natural Interaction Behavior" function:

- Frequency band (MHz): 915 and 864 (GN and CY); 915 (GE)
- Operation mode: Full Duplex
- Range:
  - Approximately 3-5m: Optimal for communication
  - Approximately 5-10m: Fade in and fade out
- Modulation: TDMA protocol

#### Near Field Magnetic Induction (NFMI):

- Transmission rate: 596 kbit/s
- Range: Approximately 50cm (20in)
- Frequency: 9.8-11.7Mhz

**Physical Characteristics:** Weight with batteries: 330g (11.6oz)

#### Environmental Characteristics:

- Operating temp: 4°F (-20°C) to 131°F (55°C)
- Shelf Life:
  - Headset: 5 years, excluding batteries
  - Batteries: 1 year
- Immersion survivability: Saltwater (5%) 30min at 2m

**Recommended Storage Conditions (<90% humidity):** 5 years: Indoor Controlled Climate (<90% humidity)

# Personal Safety Division

## Standards and Approvals

### Environmental Performance:

- Tested in accordance with MIL- STD-810G

### Electromagnetic Interference:

- Tested in accordance with MIL-STD-461G

### Hazards of Electromagnetic Radiation to Ordnance (HERO), Personnel (HERP), and Fuel (HERF):

- Evaluated against applicable limits outlined in MIL-STD-464C

Noise Reduction Rating (NRR) tested in accordance with ANSI S3.19-1974

Impulsive Peak Insertion Loss (IPIL) tested in accordance with ANSI/ASA S12.42-2010

## Laboratory Attenuation

**Table 1: ComTac VII, Headband with foam cushions, MT14H41A-300NA; CY, GE, GN**

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA Class
Mean Attenuation (dB)	14.0	19.4	27.9	32.3	31.7	39.7	44.5	40.1	41.0	22	B
Standard Deviation (dB)	2.7	3.2	2.6	2.1	2.8	3.6	3.4	2.6	2.2		

**Table 2: ComTac VII, Headband with gel cushions, MT14H41A-300NA; CY, GE, GN**

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA Class
Mean Attenuation (dB)	14.5	18.8	27.6	34.3	33.8	39.7	42.8	40.7	40.9	23	A
Standard Deviation (dB)	2.7	2.6	2.3	3.0	2.2	2.9	3.7	2.6	3.1		

U.S. EPA specifies the NRR as the measure of hearing protector noise reduction. However, 3M makes no warranties as to the suitability of the NRR for this purpose. 3M strongly recommends personal fit testing of hearing protectors. Research suggests that users may receive less noise reduction than indicated by the attenuation label value(s) on the packaging due to variation in fit, fitting skill, and motivation of the user. Refer to applicable regulations for guidance on how to adjust attenuation label values. It is recommended that the NRR be reduced by 50% to better estimate typical protection.

ComTac VII meets the single hearing protection requirement listed in DA PAM 40 501 Army Hearing Program 2015 for both steady-state and impulse noise.

# Personal Safety Division

## 3M™ PELTOR™ ComTac™ VII NIB headsets - Single versus Dual Frequency

Two versions of the NIB headset are available for purchase in the United States. Customers can purchase a single frequency, FCC approved, 915.5 MHz NIB headset. U.S Federal Government customers can also purchase a dual frequency NIB headset that is not FCC approved as it offers both 915.5 MHz (For use in North America, Australia and New Zealand) and 864 MHz (approved for use in Europe). The dual-frequency, non-FCC labeled headsets are offered to U.S. Federal Government customers who may require use of the headset outside of the United States, such as U.S. military personnel. Prior to using a NIB enabled headset, it is the user's responsibility to ensure they are using the correct NIB frequency for the region in which they are currently using the headset.

### 3M™ PELTOR™ ComTac™ VII NIB headsets - Dual frequency (915.5 and 864 MHz)

For Federal Government use only.

Part Number	Description	Legacy 3M ID	SAP ID	Color
MT14H41A-300NA CY	3M™ PELTOR™ ComTac™ VII Headset, Coyote Brown	UU010934857	7100222865	
MT14H41A-300NA GN	3M™ PELTOR™ ComTac™ VII Headset, OD Green	UU010934840	7100222738	

### 3M PELTOR ComTac VII NIB headsets - Single frequency (915.5 MHz)

For Federal and non-Federal Government use.

Part Number	Description	Legacy 3M ID	SAP ID	Color
MT14H41A-300NA GE	3M™ PELTOR™ ComTac™ VII Headset, Grey	UU010934832	7100222831	

## Accessories and Spare Parts

Part Number	Description	Legacy 3M ID	SAP ID
M194/2	3M™ PELTOR™ Wind shield Kit for surround mic	UU010955936	7100232688
1086 SV/1	3M™ PELTOR™ Battery Lid	UU010953469	7100232689
AL8002/1	3M™ PELTOR™ Downlead cable ComTac™ VII	UU010954111	7100225790
AGM/1	3M™ PELTOR™ Headband ComTac™ VII	UU010972220	7100227486
A47/1	3M™ PELTOR™ Microphone guide	UU010972238	7100227492
MT71/1	3M™ PELTOR™ Boom Microphone dyn	UU010972246	7100230581
P3ADG47-F SV/2	3M™ PELTOR™ ARC rail attachment, 1 pair	UU010972253	7100227493
HY68 SV	3M™ PELTOR™ Replacement Hygiene Kit, 1 pair	XH001659461	7000108023
HY80A	3M™ PELTOR™ Replacement Gel Rings, 1 pair	70071573656	7100014310

# Personal Safety Division

## CAUTION

When worn according to the User Instructions, this hearing protector helps reduce exposure to both continuous noises, such as industrial noises and noises from vehicles and aircraft, as well as very loud impulse noises, such as gunfire. It is difficult to predict the required and/or actual hearing protection obtained during exposure to impulse noises. For gunfire, the weapon type, number of rounds fired, proper selection, fit and use of hearing protection, proper care of hearing protection, and other variables will impact performance. If your hearing seems dulled or you hear a ringing or buzzing during or after any noise exposure (including gunfire), or for any other reason you suspect a hearing problem, your hearing may be at risk. To learn more about hearing protection for impulse noise, please visit [www.3M.com/hearing](http://www.3M.com/hearing).

## WARNING

These hearing protectors help reduce exposure to hazardous noise and other loud sounds. **Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury.** For correct use, consult supervisor and User Instructions, or contact 3M Technical Service in the U.S.A at 1-800-665-2942. If there is any drainage from your ear or you have an ear infection, consult with your physician before wearing earplugs. Failure to do so may result in hearing loss or injury.

### **Warranty:**

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office.

### **Importance Notice:**

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

3M acknowledges the respective Trademark Owners' rights in this literature.

For distribution in the USA only.



#### **Personal Safety Division**

3M Center  
Building 235-2W-70  
St. Paul, MN 55144-1000  
3M PSD products are  
occupational use only.

3M Canada  
P.O. Box 5757  
London, Ontario  
N6A 4T1

#### **In United States of America**

Technical Service: 1-800-665-2942  
Customer Service: 1-800-328-1667  
Web: 3M.com/PELTOR  
E-mail: PELTOR.comms@mmm.com

**In Canada**

Technical Service: 1-855-484-3093  
Customer Service: 1-800-410-6880  
E-mail: PELTOR.comms.canada@mmm.com

© 2026, 3M. All rights reserved. 3M and PELTOR are trademarks of 3M. Used under license in Canada. All other trademarks are property of their respective owners.