



3M™ ActiV.A.C.™ Therapy System specifications

Designed specifically for the ambulatory patient.

Specifically designed for the ambulatory patient, the 3M™ ActiV.A.C.® Negative Pressure Wound Therapy System is a lightweight, portable system that combines enhanced technology with easy-to-use features to facilitate the mobility of patients who may benefit from 3M™ V.A.C.® Therapy.

Easy-to-use therapy unit

- Simple touch-screen controls
- Quick release 300 mL canister
- Single-touch therapy on/off
- Intuitive menus simplify therapy programming and operation



3M™ SensaT.R.A.C.™ Technology and Pad

- Alarm differentiation for easier troubleshooting
- Surface designed with patient comfort in mind
- Flexible pad easily conforms to patient contours
- Low profile design fits under clothing



3M™ Seal Check™ feature

- Provides instant feedback to help identify leaks
- Helps ensure accurate seals
- Easy troubleshooting for patients may reduce unscheduled caregiver visits



Therapy history report

- Allows clinicians to monitor and track therapy settings, alarm history, therapy dates and times, dressing and canister changes and record the number of pieces of foam used

Patient History

Date	Time	Event
12 Mar 2006	23:12:30	Infection Clear
12 Mar 2006	23:12:00	Infected
12 Mar 2006	20:12:51	New Dressing
12 Mar 2006	20:11:00	Healing +1
12 Mar 2006	02:12:40	Healing
12 Mar 2006	02:12:00	Wound Dressed

Setting guide

- Aligned with 3M™ V.A.C.® Therapy clinical guidelines
- Preset therapy settings by wound type eases setup
- Step-by-step guide simplifies setup for infrequent users

Select Wound Type

Pressure Ulcers



3M™ ActiV.A.C.® Therapy System Specifications

ActiV.A.C. Therapy System part number: #340013

Weight: 2.4 lbs (1.08 kg) with an empty canister

Dimensions: 7.6" W x 6" H x 2.5" D (19.3 × 15.2 × 6.4 cm)

Battery type: Lithium-ion rechargeable battery

Battery life: 14 hour average

Recharging time: 6 hours to reach full charge from a completely discharged state

Canister size: 300 mL

Therapy delivery modes: Continuous or Intermittent

Intensity settings: Low, Medium, High

Therapy pressure options: Negative Pressure: -25 mmHg through -200 mmHg
(-3.3 kPa to -26.6 kPa)

Carrying case: The black nylon design allows for full touch screen navigation, battery charging, and tubing storage without removing the ActiV.A.C. Therapy Unit from the case. The case has an adjustable, padded strap and a belt loop that allows the unit to be worn in multiple orientations.



Electrical data:

External Power Supply Input: 100-240 VAC .72 A @ 115 VAC 47-63 Hz

External Power Supply Output: 12 V, 3.3 A

Patient and Enclosure Leakage Current: <100 Microamps

IEC classification:

Type B, Applied Part, Class II, IPX0: Equipment not suitable for use in presence of flammable anesthetic mixture with air, oxygen or nitrous oxide

Storage conditions:

Temperature range: -4°F (-20°C) to 140°F (60°C)

Relative humidity range: 0-95% non-condensing

Operating conditions:

Temperature range: 41°F (5°C) to 104°F (40°C)

Relative humidity range: 0-95% non-condensing

Altitude range: 0 to 14,000 feet (0 to 4267 m)

Optimum performance: 0 to 8,000 feet (0 to 2438 m)

For more information about 3M™ V.A.C.® Therapy contact your local 3M representative at **1-800-668-5403** or visit us online at: **3M.ca/Medical**

Note: Specific indications, contraindications, warnings, precautions and safety information exist for these products and therapies. Please consult a clinician and product Instructions for Use prior to application. This material is intended for healthcare professionals.



Available in Canada from your authorized 3M+KCI distributors.

KCI USA, Inc., a 3M Company

KCI owned and operated by 3M Company

KCI Medical Canada, Inc.
75 Courtneypark Dr., W.,
Unit 4
Mississauga, ON
L5W 0E3

KCI USA, INC.
12930 IH 10 West
San Antonio, TX
78249

© 2022 3M. All rights reserved. 3M and the other marks shown are marks and/or registered marks. Unauthorized use prohibited. Used under license in Canada.
CA_EN_70-2013-1439-3 2206-24352-E