





Goes on from 0° to 150° F



No primer required



Highly compatible with other materials



High-tack acrylic adhesive



ncreased opacity



Clean look and visibility

Larger Sizes

SAP Material	Dimensions	Material Description	Rolls/Case	Rolls/Pallet
7100232801	36 in x 75 ft	Solid	1	42
7100232532	48 in x 75 ft	Solid	1	25
7100232544	60 in x 75 ft	Solid	1	25

Smaller Sizes (Flashing Tape)

SAP Material	Dimensions	Material Description	Rolls/Case	Rolls/Pallet
7100232547	2 3/8 × 75 ft	Solid	20	540
7100232553	4 in x 75 ft	2-2 Split	12	324
7100284872	4 in x 75 ft	Solid	12	324
7100232543	6 in x 75 ft	3-3 Split	8	216
7100232548	6 in x 75 ft	2-4 Split	8	216
7100284873	6 in x 75 ft	Solid	8	216
7100232577	9 in x 75 ft	2-7 Split	4	192
7100284869	9 in x 75 ft	Solid	4	192
7100232800	12 in x 75 ft	2-10 Split	4	108
7100285923	12 in x 75 ft	Solid	4	108
7100232799	18 in x 75 ft	7-11 Split	1	50
7100232551	18 in x 75 ft	Solid (Made to order)	1	50

3M has additional products to fulfill your other building and construction needs. To learn more and connect with our team, please visit our website or contact your local 3M sales rep.

Additional 3M Air and Vapor Barrier Systems



3M[™] Air Barrier with Permeable Backing 3015VP

- Top Liner Technology with exposed adhesive and lightweight rolls allows for fast application and single-person installation.
- Exceptional pressure sensitive adhesive allows for immediate repositioning, with adhesion increasing over time resulting in strong and long-lasting bonds.
- Up to 12-month UV exposure providing more flexibility for long-running projects or unexpected delays.

SAP Material	Dimensions	Rolls/Case	Rolls/Pallet
7100358378	6in x 100ft	1	
7100334285	15in x 100ft	1	50
7100334107	30in x 100ft	1	30
7100334468	60in x 100ft	8	25



3M™ Ultra Conformable Tape 3015UC

- Extremely flexible tape stretches horizontally and vertically and conforms around corners.
- Enables up to 40% faster window and door detailing.

SAP Material	Dimensions	Material Description	Rolls/Case	Rolls/Pallet
7100171852	6 in x 75 ft	Solid	2	72
7100093404	9 in x 75 ft	Solid	1	48

3M™ Air & Vapor Through Wall Flashing Tape 3015TWF

- Exceptional puncture and abrasion resistance.
- Specially designed for use as a through wall flashing and damp-proof course.



SAP Material	Dimensions	Material Description	Rolls/Case	Rolls/Pallet
7010336161	4 in x 25 yd	1-3 Split	12	324
7100093380	6 in x 75 ft	2-4 Split	8	216
7100101193	9 in x 25 yd	4-5 Split	4	144
7100054224	12 in x 75 ft	2-10 Split	4	108
7100054220	18 in x 75 ft	7-11 Split	1	50

VTS6 3M™ Printed Squeegee

SAP Material	Dimensions	Material Description	Units/Case	Rolls/Pallet
7100232701	3 in x 6 in	Solid	250	_

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.

Learn more at 3M.com/airbarrier and connect with your 3M specialist today.

