

3M™ Liqui-Cel™ MM-1.7×8.75 Series Membrane Contactor

Typical Properties

Membrane Characteristics	
Cartridge Configuration	Parallel Flow. Lumenside Liquid Flow.
Liquid Flow Guidelines	< 3000 ml/min
Membrane Type	X50 Fibre
Membrane/Potting Material	Polypropylene/Polyurethane
Priming Volume (approximate)	
Shellside	140 ml
Lumenside	70 ml

Pressure Guidelines*	
Maximum Lumenside LIQUID	5-20°C, 4.1 barg (41-68°F, 60 psig)
Working Temperature/ Pressure	40°C, 2.1 barg (104°F, 30 psig)


* Note: Liquid pressure should always exceed gas pressure.

Housing Options and Characteristics	
Material	Polycarbonate
Flange Connections	
Shellside (gas/vacuum)	Standard Female Luer Lock <i>Supplied with two ¼ inch Hosebarb adaptors which mate to ¼ inch ID tubing</i>
Lumenside (wetted surface)	¼ inch FNPT

Seal Options	
Material	Applications
EPDM	All Purpose


Weight (approximate)	
Dry	186 grams

Regulatory	
Complies with the limits as set by (EU) 2015/863 amending Annex II to the Restriction on Hazardous Substances (RoHS) Directive (2011/65/EU). 3M™ Liqui-Cel™ MM-1.7×8.75 Series Membrane Contactors are constructed of FDA Title 21 CFR § 174-186 compliant materials for wetted parts only at ambient temperatures.	




Note: All dimensions are nominal values. See full housing drawing on 3M.ca/Liqui-Cel for additional details.

3M™ Liqui-Cel™ MM-1.7×8.75 Series Membrane Contactor



— DO Removal — Vacuum Volume (estimated)



Curves represent nominal values, generated using water on the Lumenside at 20°C with 50 torr of vacuum drawn on both Shellside ports. The estimated vacuum volume guideline is based on a flow rate at 20°C, 50 Torr. Characteristics may change under different operating conditions.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M, 3M Science. Applied to Life. and Liqui-Cel are trademarks of 3M. All rights reserved. Used under license in Canada. © 2022, 3M. All other trademarks are the property of their respective owners. 2212-25351c E



3M Separation and
Purification Sciences Division
3M Canada
300 Tartan Drive
London, Ontario N5V 4M9
Canada
1-800-443-1661

Rev. 12/2022
[3M.ca/Liqui-Cel](https://www.3M.ca/Liqui-Cel)