



[Product Details](#)



[Regulatory Info/SDS](#)

Technical Data Sheet

3M™ ScotchPad™ Tape Pad 3750P

Product Description

3M™ ScotchPad™ Tape Pad 3750P is a pre-cut pad formed with layered, high performance tape sheets featuring durable 3M™ Scotchpro™ film backing that is strong, conformable, and resistant to impact shock. Tape sheets are coated with an aggressive adhesive to provide excellent holding power to many surfaces. Each piece of tape is coupled with a strip of liner material for easy handling and application, without the need for a dispenser.

Product Features

- Release liner tab.
- Pre-cut individual sheets.
- 25 layered sheets to each back sheet.
- Strong, abrasion resistant.
- Weather resistant and long aging.
- Easy removal of a single sheet.
- Easy removal of liner upon application.
- Portable and lightweight.
- Convenient and space-saving.
- Dust-free adhesive surface.
- Exact replication.
- Helps prevent labels from being scuffed off.
- Guards information against weather damage.
- High visibility or label legend.
- Helps prevent labels from yellowing or drying out during normal label life.
- Holds tight to most cartons and containers.
- Protects and allows for bar code read.
- Proper positioning and wrinkle-free application.
- Quick, efficient usage.
- Easy to carry sheets in pad form.
- Easy to store in pockets, drawers and on desk tops.
- Secure, consistent applications.
- Labor saving.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Color		Transparent, tan
Adhesive Type		Pressure sensitive hot melt rubber resin
Backing		3M™ Scotchpro™ biaxially oriented polypropylene film
Total Tape Thickness	ASTM D3652	0.079 mm (3.1 mil)
Backing Thickness	ASTM D3652	0.051 mm (2 mil)

Attribute Name	Value
----------------	-------

Attribute Name	Value
Available Formats	25 Sheets Per Pad
	40 Pads per Carton
	5 Cartons per Case
	200 Pads per Case
	5000 Applications per Case

Typical Performance Characteristics

Attribute Name	Test Method	Temperature	Test Condition	Substrate	Value
180° Peel Adhesion	ASTM D3330	23 °C (73 °F)			6 N/cm (55 oz/in) ¹
Elongation at Break	ASTM D3759				160 %
Tensile Strength	ASTM D3759		Machine Direction		61 N/cm (35 lb/in)
Tensile Strength	ASTM D3759		Cross Direction		122.6 N/cm (70 lb/in)
Tensile Strength	ASTM D3759				61.3 N/cm ²
Holding Power	ASTM D3654			Fiberboard	12,000+ min

¹ 300 mm/min (12 in/min)

² Machine Direction

Handling/Application Information

Application Techniques

3M™ ScotchPad™ Tape Pad 3750P should be removed one at a time by grasping the end with a liner and pulling the sheet free from the pad. Place the far end of the sheet in the desired location and allow the sheet to adhere from that end back to the tabbed end. Flip out the tab and press the whole sheet flat. The pad can be adhered in a convenient location when the back sheet of the pad is peeled away and the pad is placed on a vertical surface or on a table, then only one hand is needed to dispense tape sheets for use.

Application of ScotchPad Tape Pad 3750P is easiest at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, tape sheets perform well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

Storage and Shelf Life

Store under normal conditions of 4° to 27°C (40° to 80°F) and 40 to 50% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 18 months from date of manufacture.

Available Sizes

Attribute Name	Value
Standard Size	2 in x 6 in

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations,

may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging.

3M™ Industrial Specialties Division
3M Center, St. Paul, MN 55144-1000
www.3M.com

©3M 2025 (4/25)