



Technical Data Sheet

3M™ Scotch® General Purpose Cloth Tape
393



[Product Details](#)



[Regulatory Info/SDS](#)

Product Description

Scotch® General Purpose Cloth Tape 393 is a polyethylene coated cloth backing coated with a rubber adhesive for moisture-proofing, duct sealing and general purpose applications.

Product Features

- High-tack, conformability, strength and easy tear properties.
- Typically used at room temperature, but will function up to 200°F (93°C) for up to 1 hour.
- Polyethylene coated cloth backing that provides a good vapor barrier to prolong tape bond.
- High tensile backing for demanding applications.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

| Attribute Name | Test Method | Value |
|----------------------|-------------|---------------------------|
| Color | | Silver |
| Adhesive Type | | Rubber |
| Backing | | Polyethylene coated cloth |
| Total Tape Thickness | ASTM D3652 | 0.3 mm (12 mil) |

Typical Performance Characteristics

| Attribute Name | Test Method | Temperature | Value |
|-----------------------------------|-------------|---------------|-----------------------------------|
| 180° Peel Adhesion | ASTM D3330 | 23 °C (73 °F) | 10.4 N/cm (95 oz/in) ¹ |
| Elongation at Break | ASTM D3759 | | 8 % |
| Tensile Strength | ASTM D3759 | | 63 N/cm (36 lb/in) |
| Short Term Temperature Resistance | | | 93 °C (200 °F) ² |

¹ 304 mm/min (12 in/min)

² Short Term (minutes, hour)

Handling/Application Information

Application Examples

- Reducing noise transmission when used as a flexible connector.
- Sealing fiberglass insulation or to cover thermal insulation.
- A waterproof covering over pipe insulation.
- Many sealing and general purpose industrial applications.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 12 months from date of manufacture.

Available Sizes

| Attribute Name | Value |
|-----------------------|----------------|
| Standard Roll Length | 54.8 m (60 yd) |

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

©3M 2024 (9/24)