



Technical Data Sheet

3M™ High Temperature Paint Masking Film 7302



[Product Details](#)

Product Description

3M™ High Temperature Paint Masking Film 7302 is a high performance, high temperature wide area masking film that is designed to not scratch or damage surfaces and is flexible for good drape and conformability.

Product Features

- 3M™ High Temperature Paint Masking Film 7302 is ideal for protecting against bleed-through of solvents and paints.
- Available as roll goods, perforated sheets on a roll, or preformed bags on a roll.
- Conformable film with good drape properties.
- Eliminates flying fiber contamination normally associated with fibrous paper wide area masking products.
- Treated backing for good paint adhesion.
- Many 3M masking tapes have excellent adhesion to 3M™ High Temperature Paint Masking Film 7302.
- Masking tape and film can be dispensed together using existing 3M apron tapers.
- Temperature Resistance of 160C up to 45 minutes.
- Smooth film that helps prevent scratching and damage to underlying substrates.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Value
Color	Translucent
Backing	laminated polymer
Density	0.945 g/cm ³
Film Thickness	0.03 mm (1.2 mil)

Typical Performance Characteristics

Attribute Name	Test Method	Test Condition	Value
Elongation at Break	ASTM D882	Machine Direction	minimum 400 %
Elongation at Break	ASTM D882	Cross Direction	minimum 500 %
Tensile Strength	ASTM D3759		10 N/cm (60 oz/in)
Short Term Temperature Resistance			160 °C (320 °F) ¹

¹ Short Term (minutes, hour)

Electrical and Thermal Properties

Attribute Name	Value
Surface Resistivity	minimum 10 ¹⁰ Ω

Handling/Application Information

Application Examples

- Tutone paint masking for automobiles, trucks, buses and boats.
- Repair painting of automobiles and trucks.
- Automotive fascia piece part paint masking.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 18 months from date of manufacture.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd