



Technical Data Sheet

Scotch™ Ultimate Paint Edge Masking Tape 2460



[Product Details](#)

Product Description

Scotch™ Ultimate Paint Edge Masking Tape 2460 has a thin, yet strong, smooth paper backing, that when used for paint masking gives a sharp paint line with a low paint ridge. Adhesive is a high temperature resistant acrylic. A low peel force also makes this tape a good choice for surface protection, longer duration, and delicate surface applications. It can be used outdoors for up to 21 days.

Product Features

- Sharp paint lines, with good resistance to solvent and latex paints.
- Has good instant adhesion for paint masking.
- High temperature resistant, up to 300°F (150°C) for 30 minutes with clean removal.
- Acrylic adhesive provides UV resistance, allowing outdoor use for up to 21 days with clean removal from most surfaces
- Minimal adhesion build over time makes this a good choice as a protective tape.
- Low peel force is good for use on delicate surfaces.
- Translucent backing aids in seeing has been properly rubbed down to give best paint line.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Color		Yellow
Adhesive Type		Acrylic
Backing		smooth Washi paper
Total Tape Thickness	ASTM D3652	0.08 mm (3.3 mil)

Typical Performance Characteristics

Attribute Name	Test Method	Temperature	Test Condition	Value
180° Peel Adhesion	ASTM D3330	22 °C (72 °F)		0.9 N/cm (8 oz/in) ¹
Elongation at Break	ASTM D3759			6 %
Tensile Strength	ASTM D3759			31.5 N/cm (18 lb/in)
Temperature Use Range			Removable Application	149 °C (300 °F)

¹ 12 in/min (300 mm/min)

Handling/Application Information

Application Examples

- Masking of straight lines and broad curves, from latex or solvent based paints.
- Masking of delicate surfaces
- Protecting surfaces from scuffing
- Protecting delicate EPDM moldings

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 24 months from date of manufacture.

Available Sizes

Attribute Name	Value
Standard Roll Length	54.8 m (60 yd)

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iata

Scotch is a registered trademark of 3M.
©3M 2024 (6/24)