



Technical Data Sheet

3M™ Cylinder Adhesive Remover



[Product Details](#)



[Regulatory Info/SDS](#)

Product Description

3M™ Adhesive Remover (Cylinder) is a citrus based cleaner that is ideal for the removal of adhesive residue for surface preparation prior to use of adhesive. It can be used for cleaning and purging cylinder hoses and applicators, cleaning heavy oils, greases, silicone, tar and paraffinic materials such as wax. It is packaged in a convenient, portable, no maintenance aerosol cylinder.

Product Features

- Formulated to replace virtually all commonly used solvents in hand-wipe cleaning processes including: 1,1,1-trichloroethane, acetone, isopropyl alcohol, lacquer thinner, methylene chloride, methyl ethyl ketone, mineral spirits, naphtha, toluene, xylene and others.
- Evaporates more slowly than the mentioned chemicals, which can result in substantially lower overall chemical use volume and the resulting VOC emissions. Also, rags and wipe-towels do not dry out as rapidly between uses and normally do not need to be as wet as with the highly volatile chemicals mentioned.
- Evaporates cleanly, leaving no/minimal non-volatile residue.
- Mild, pleasant citrus odor.
- Offers an easy way to clean and purge cylinder applicators and hoses.
- Useful for cleaning and surface preparation prior to bonding, coating or further processing of parts.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Uncured Physical Properties

Attribute Name	Value
Base	Citrus Extract

Typical Physical Properties

Attribute Name	Value
Appearance	Colorless to Light yellow
Odor	Mild Citrus
Solubility in Water	Nil
Boiling Point	≤68 °F
Flash Point	-50 °F
VOC	800 g/L
Hazardous Air Pollutants (HAPS)	0 % by weight

Handling/Application Information

Application Techniques

Caution! This product should not be used as a hand cleaner and skin contact should be avoided. This product may cause skin irritation upon prolonged or repeated contact. Do not rinse into waterways or sewers.

Application Temperature:

For best results, the temperature should be between 60°-80°F (16°-27°C). Temperatures outside this range may affect sprayability.

Equipment Setup:

Attach the larger flare fitting end to the spray applicator and tighten the nut securely. Check to see that the applicator gun trigger stop/adjusting nut is fully locked against the trigger. Attach the other end of the hose, a smaller flare fitting, to the cylinder valve and tighten securely.

Cleaning Parts or Surfaces:

Hold the applicator 6-10 inches away from the surfaces to be cleaned and spray an even coat (the smaller the spray pattern, the closer the applicator gun will need to be to the surface). Thoroughly coat the surfaces to be cleaned. Wait a few minutes for product to completely penetrate and loosen the adhesive. Use a scraper or cloth to clean up the residue. Repeat this process as needed.

Cleaning Cylinder Spray Equipment:

For routine cleanup and maintenance – Attach the spray hose and applicator assembly to the cylinder. Slowly open the cylinder valve and inspect the connections for any leaks. Tighten if needed. Fully open the valve. Spray the 3M™ Scotch-Weld™ Adhesive Remover through the system into a pail or some other form of waste material. When finished, turn the valve on the cylinder to the closed position and purge the hose and applicator until nothing more comes out. Remove the hose and applicator assembly from the cleaning cylinder and replace onto an adhesive cylinder.

Compatibility:

3M Adhesive Remover is compatible with virtually all metals, as well as many plastics and elastomers. 3M recommends that you test compatibility with the particular materials in question under your actual use conditions. TEST FOR COMPATIBILITY of surfaces to assure this product will not attack the surface. NOTE: This product will attack some plastics.

Note:When using solvents, extinguish all ignition sources, including pilot lights, and follow the manufacturer's precautions and directions for use.

Application Equipment

Description	3M ID Number
3M™ Cylinder Adhesive Applicator (includes 9501 tip)	62-9880-9930-5
Cylinder Adhesive Applicator H (includes 4001 tip) – this applicator is for use with 3M™™ Cylinder 94 CA	62-9880-9950-3
Cylinder Adhesive Applicator EX (with 18" Extension and 9501 Tip)	62-9880-9940-4
Cylinder Adhesive 6 Foot Hose	62-9880-0006-3
Cylinder Adhesive 12 Foot Hose	62-9880-0012-1
Cylinder Adhesive 25 Foot Hose	62-9880-0025-3
Cylinder Adhesive 50 Foot Hose	62-9880-0050-1
Cylinder Adhesive 250050 Spray Tip	62-9880-8133-7
Cylinder Adhesive 4001 Spray Tip	62-9880-4001-0
Cylinder Adhesive 650050 Spray Tip – this nozzle has half the output of the 6501 nozzle	62-9880-8173-3
Cylinder Adhesive 6501 Spray Tip	62-9880-6501-7
Cylinder Adhesive 730154 Spray Tip – this nozzle minimizes dripping on 3M™™ Cylinder 60 CA	62-9880-7301-1
Cylinder Adhesive 9501 Spray Tip	62-9880-9501-4
Cylinder Adhesive QSS Spray Tip – this nozzle is needed for 3M™™ Cylinder 70	62-9880-8148-5
Cylinder Adhesive T-Fitting	62-9880-8348-1
Cylinder Adhesive Hose Swivel	62-9880-7948-9

Applicator Suggestion: 3M™ Cylinder Adhesive Applicator (62-9880-9930-5) is suggested for 3M™ Adhesive Remover Cylinder.

Nozzle Suggestions:

	250050	4001	650050	6501	730154	9501
Spray Pattern (inches): (see *Note below)	1-4	2-6	3-8	3-8	4-10	5-12
Applications:	Restricted output (General)	General	Restricted output (General)	General	Minimizes dripping	General

*Note: Spray pattern widths will vary between products, due to formulation and pressure differences.

Spray Pattern Adjustments: Unscrew the trigger stop/adjusting nut away from the trigger 3-4 turns and spray a test pattern. For more output and a wider spray pattern, continue to unscrew the nut away from the trigger. For less output and smaller spray pattern, screw the adjusting nut back towards the trigger. Hold the applicator 6-10 inches away from the surfaces to be sprayed and apply a uniform coat. (The smaller the spray pattern, the closer the applicator gun will need to be to the surface).

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) in the original, unopened packaging, out of direct sunlight. For best performance, use this product within 24 months from date of manufacture.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577

Automotive Disclaimer

Select Automotive Applications:

This product is an industrial product and has not been designed or tested for use in certain automotive applications, such as automotive electric powertrain battery or high voltage applications, which may require the product to be manufactured in a IATF certified facility, meet a Ppk of 1.33 for all properties, undergo an automotive production part approval process (PPAP), or fully adhere to automotive design or quality system requirements (e.g., IATF 16949 or VDA 6.3). Customer assumes all responsibility and risk if customer chooses to use this product in these applications.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of

a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

3M trademarks of 3M Company.
©3M 2024 (8/24)