



Technical Data Sheet

3M™ Solvent No. 2



[Product Details](#)



[Regulatory Info/SDS](#)

Product Description

3M™ Solvent No. 2 can be used for removing oil soluble or oil resistant adhesives, coatings or sealers.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Uncured Physical Properties

Attribute Name	Value
Net Weight	6.3 to 6.7 lb/gal

Typical Physical Properties

Attribute Name	Value
Solvent Resistance	Petroleum Distillate, N-Hexane and Toluene
Flash Point	-25 °C (-14 °F)

Handling/Application Information

Directions for Use

Cleaning: Cleanup excess adhesive, coating or sealer with suggested 3M™ Solvent. Clean application equipment immediately after use and wipe dry. In some cases, it may be necessary to soak parts overnight. NOTE: These solvents may attack certain types of plastic or rubber. Test for compatibility before using.

Note: When using solvents, extinguish all ignition sources, and follow the manufacturer's precautions and directions for use.

Compatibility

Use 3M™ Solvent No. 2 for cleanup of:

- 3M™ Neoprene Contact Adhesive 5 3M™ Neoprene Contact Adhesive 10
- 3M™ Water Based Acrylic Sealant 606 NF* 3M™ Nitrile Industrial Sealant 800
- 3M™ Duct Sealer 900
- 3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300 3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300L 3M™ Neoprene High Performance Contact Adhesive 1357
- 3M™ Neoprene High Performance Contact Adhesive 1357L 3M™ Industrial Adhesive 1870
- 3M™ Neoprene Rubber and Gasket Adhesive 2141 3M™ General Purpose Construction Mastic 4323 3M™ Industrial Adhesive 4550
- 3M™ High Performance Industrial Plastic Adhesive 4693 3M™ Industrial Adhesive 4799
- 3M™ Marine Adhesive Sealant 5200**
- 3M™ Butyl Sealant Tape 5422 3M™ Butyl Sealant Tape 5423

Note: If a 3M product is not listed, refer to 3M product data sheet for information about recommended cleanup solvent.

*These products may be removed when wet with warm, soapy water. Use the suggested solvent for removal of dry product.

**These products cannot be easily removed after curing. Use the suggested solvent for removing uncured material.

Storage and Shelf Life

Store product at 60-80°F (15-27°C) for maximum storage life.

When stored in the original, unopened container at the recommended storage conditions, these products have a shelf life of 24 months.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577 or (651) 737-6501.

Automotive Disclaimer

Select Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, such as automotive electric powertrain battery or high voltage applications, which may require the product to be manufactured in a IATF certified facility, meet a Ppk of 1.33 for all properties, undergo an automotive production part approval process (PPAP), or fully adhere to automotive design or quality system requirements (e.g., IATF 16949 or VDA 6.3). Customer assumes all responsibility and risk if customer chooses to use this product in these applications.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M
Industrial Adhesives and Tapes Division
3M Center, Building 225-35-06
St. Paul, MN 55144-1000
800-362-3550

3M trademarks of 3M.
© 3M 2022 (5/22)