



Technical Data Sheet

3M™ Durable Label Material 7850HL



[Product Details](#)

Product Description

3M™ Durable Label Material 7850HL is a matte radiant white polyester label stock that offers excellent moisture resistance and thermal stability. This label product utilizes 3M™ Adhesive 350 which is a versatile adhesive for label material that offers excellent chemical resistance and holding strength even at high temperatures.

Product Features

- Adhesive can permanently bond to high surface energy (HSE) and low surface energy (LSE) plastics, textured and contoured surfaces, powder coatings, and slightly oily metals.
- Topcoated polyester provides excellent toner anchorage. It is also receptive to dot matrix printing and is hand writeable. The matte coating resists degradation from scuffing, chemicals, moisture, and wide temperature fluctuations. The topcoat also provides improved ink anchorage for traditional forms of press printing.
- UL recognized (File MH16411). See the UL listings for details.
- Meets British Standard BS-5609.
- Ambient temperatures and humidity levels will impact lay flat properties of label material. Store unconverted label stock in controlled environment of 70°F (21°C) and 50% relative humidity.
- 78# CCK liner is designed for sheet fed laser toner products and is backside printable. To test lay flat properties of converted material, place in controlled environment described above. Converted laser sheet will acclimate and return to lay flat state. Slight curl may occur as a result of heat exposure through the laser print but should not affect processing in many laser printers.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Value
Adhesive Type	#350 Acrylic
Facestock	Matte Radiant White Polyester

Attribute Name	Value
Adhesive Thickness	0.028 mm (1.1 mil)
Facestock Thickness	0.058 mm (2.3 mil)
Liner	78# Clay Coated Kraft
Liner Thickness	0.117 mm (4.6 mil)

Attribute Name	Value
Convertability	In order to capture the superior performance properties of 3M™ High Holding Acrylic Adhesive 350, thicker calipers are utilized for LSE or textured substrates. Its higher caliper, while desirable for the end use applications, may require extra care during processing.

Typical Performance Characteristics

180° Peel Adhesion

Temperature: 23 °C (73 °F)
Test Method: ASTM D3330

Dwell Time	Substrate	Value
10 min	Polycarbonate (PC)	7.7 N/cm (70 oz/in) ¹
10 min	Polypropylene (PP)	4.5 N/cm (41 oz/in) ¹
10 min	Stainless Steel	7.9 N/cm (72 oz/in) ¹
72 h	Polycarbonate (PC)	8.2 N/cm (75 oz/in) ¹
72 h	Polypropylene (PP)	5.5 N/cm (50 oz/in) ¹
72 h	Stainless Steel	9.1 N/cm (83 oz/in) ¹

¹ 304 mm/min (12 in/min)

Attribute Name	Value
Minimum Application Temperature	10 °C (50 °F)
Long Term Temperature Resistance	149 °C (300 °F) ¹
Minimum Long Term Temperature Resistance	-40 °C (-40 °F) ¹

¹ Long Term (day, weeks)

Attribute Name	Value
Note	Calipers are nominal values

Typical Environmental Performance

180° Peel Adhesion

Temperature: 32 °C (90 °F)
Dwell Time: 24 h
Test Method: ASTM D3330
Environmental Condition: 90%RH

Substrate	Value
High Density Polyethylene (HDPE)	4.3 N/cm (39 oz/in) ¹
Polycarbonate (PC)	5.8 N/cm (53 oz/in) ¹
Polypropylene (PP)	3.9 N/cm (36 oz/in) ¹
Stainless Steel	10.1 N/cm (92 oz/in) ¹

¹ 304 mm/min (12 in/min)

Typical Environmental Characteristics

Humidity Resistance

24 hours at 100°F (38°C) and 100% relative humidity: no significant change in appearance or adhesion

Printing

Facestock is topcoated for improved ink receptivity and is designed for laser toner and dot matrix printing. It is printable by all standard roll processing methods including flexography, hot stamp, letterpress, and screen printing.

Converting

Designed for rotary die cutting. Use sharp rotary dies tooled for the specific label material. Avoid stacking fanfolded labels higher than three or four inches.

Handling/Application Information

Application Examples

- Barcode labels and rating plates.
- Property identification and asset labeling.
- Warning, instruction, and service labels for durable goods.
- Nameplates and durable goods.

Application Techniques

- For maximum bond strength, surface should be thoroughly cleaned and dried. A typical cleaning solvent is heptane or isopropyl alcohol. Note: Follow the manufacturer’s precautions and directions for use when using solvents.
- For best bonding conditions, application surface should be at room temperature or higher. Low temperature surfaces, below 50°F (10°C), cause the adhesive to become firm and will not allow the adhesive to flow and develop intimate contact with the substrate.
- Higher initial bonds can be achieved through increased rubdown pressure. Use a rubber roller with maximum hand pressure for best results.

Industry Specifications

UL Recognized (File MH16411)
CSA Accepted (File 99316)

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 24 months from date of manufacture.

Available Sizes

Attribute Name	Value
Packaging	Finished labels should be stored in plastic bags.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M’s control and uniquely within user’s knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer’s application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the

product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

3M is a trademark of 3M Company.
Alconox is a registered trademark of Alconox, Inc.
409 is a registered trademark of Clorox.
©3M 2024 (9/24)