

## **Technical Data Sheet**

Effective: 14/08/2024 Supersedes: 28/02/2020

## **Automotive Aftermarket Division**

## 3M<sup>™</sup> 471LA Hookit<sup>™</sup> Trizact<sup>™</sup> Clear Coat Sanding Disc-P1500

#### 1) Part Numbers

02088 - 150 mm 02094 - 75 mm

#### 2) Description and end uses

Designed to remove paint defects such as nibs and orange peel, use damp to reduce dust production and premature loading.

#### 3) Physical Properties

Backing : 3 mil Polyester Film Backing

Mineral : Aluminium Oxide

Grade range : Grade 1500

Coating : Trizact construction

Bonding : Waterproof Resin Bonding

Attachment : Hookit™ Discs

Conversion Form : 150 mm/75 mm Hookit™ Discs

Feature	Benefits
Film Backing	Extended Life
	Improved quality
Trizact mineral technology to allow	Longer Life -
good performance	Increased efficiency & productivity
Desired finish level	Improved quality
Used damp-with minimal water spray.	Longer life and minimal cleaning after
	use.
Use with interface	Increased Productivity.
	Improved quality
Machine method	Increased productivity



## **Technical Data Sheet**

Effective: 14/08/2024 Supersedes: 28/02/2020

#### 4) Directions for Use

- Ensure that the painted surface is cleaned thoroughly. Loose dirt on the surface or the disc can result in severe scratches to the paint surface.
- Use product damp by spraying water onto the paint surface from a spray bottle before sanding to matt surface.
- For contoured panels or ones with styling lines use on an interface pad this gives increased flexibility and reduces the danger of cutting through edges.
- Always use the product damp but not too much water to extend disc life dry or too little water makes the disc load. Excess water will result in the product skating across the surface without proper matting action.
- Run the sander at medium speed (too fast can cause risk of sanding through at edges). Sand areas twice to complete matting.

#### 5) Storage

It is recommended that all Coated Abrasive Products should be stored at constant levels of temperature and humidity within the ranges of 18-22°C, 35-50% RH. They should be kept away from damp (or cold) walls, windows or floors to avoid possible moisture absorption. Equally storage adjacent to heat sources e.g. steam pipes, radiators, hot air ducts, ovens, etc, should be avoided.

Product is best stored in original packaging until ready for use. Shelf Life is indefinite under these ideal storage conditions.

### 6) Safety

Whenever possible, sanding should be carried out in a well-ventilated area and it is strongly recommended that suitable goggles, dust mask and gloves are worn. Discs should be used only on machines with a suitable back-up pad designed for the purpose and maintained in good condition at all times.

The abrasive discs should extend symmetrically to no more than 2 mm beyond the outer rim of the back-up pad.

Damaged or misshapen abrasive discs or back-up pads should not be used. Discs and pads should not be modified in any way. They should be used only in their original size and shape, as supplied.

It is recommended that discs be used only on back-up pads that are clearly marked with maximum permitted running speed (MOS). The speed stated should not be exceeded.

Machines should be operated with the disc making the shallowest angle possible with the work piece. Care should be taken to ensure that discs are mounted centrally on the back-up pad.



## **Technical Data Sheet**

Effective: 14/08/2024 Supersedes: 28/02/2020

When not in use, disc sanding machines should be placed in a stand designed for the purpose or, alternatively, positioned on their backs. They must not be placed with the disc or pad face in contact with the floor or workbench.

3M™ 471LA Hookit™ Trizact™ Clear Coat Sanding Disc-P1500 is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.

#### 7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

# **3M**

## **Technical Data Sheet**

Effective: 14/08/2024 Supersedes: 28/02/2020

#### For Additional Health and Safety Information

3M South Africa & Sub-Saharan Africa, 146A Kelvin Drive, Woodmead, Sandton, South Africa, Tel: (0861) 225536

3M (East) AG Representation Office Tirane, Rruga Sami Frasheri, Pallati i Ri Perxhola Kati 2 Ap2, 1000 Albania

3M Arabia, LLC, Building 24-25 3M Saudi Arabia Zone C, Business Gate, Airport Road, Riyadh, Saudi Arabia

3M Bulgaria, Mladost 4, Business Park, bl.4, 2nd floor, Sofia 1766, Bulgaria

3M Česko, spol. s r.o., V Parku 2343/24, 148 00 - Praha 4, Czech Republic

3M (East) AG, Branch office Croatia, Avenija Većeslava Holjevca 40, 10 000 Zagreb, Croatia, Tel: +385 1 2499750, www.3m.com.hr

3M Egypt, Finance Center, New Cairo, Plot 140, Banking Sector, 5th settlement, Cairo, Egypt

3M Hellas MEPE, Automotive Aftermarket Division, 20 Kifisias Avenue, 151 25 Marousi, Greece,

Phone: +30 210 68 85 300, innovation.gr@mmm.com, www.3M.gr

3M Hungária Kft, Neumann János u. 1/E, 1117 Budapest, Hungary

3M Israel, 91 Medinat Hayehudim St., Herzliya, Israel

3M Kenya Ltd, Victoria Towers, 3rd Floor, Kilimanjaro Av, Upperhill, Kenya

3M Gulf Limited, Ein El Mreisseh, Saint Charles City Center, 4th. Floor, P.O.Box: 11-5025, Riad el Solh, Beirut 1107 2180 Lebanon

3M Minnesota Mining & Manufacturing Nigeria Limited, No 2 Sheraton Opebi Link Road, Ikeja, Lagos Nigeria

3M Pakistan, Islamic Chamber of Commerce Building, ST-2/A, Block 9, KDA Scheme 5, Clifton, Karachi, Pakistan

3M Poland, Al. Katowicka 117, Kajetany, 05-830 Nadarzyn, Poland, Telefon: +48 22 739 60 00, www.3m.pl/kontakt

3M Gulf (Representation Office), Suhaim Bin Hamad St., Al Mana Towers Tower B, 2nd Floor, Office No.4, Doha Qatar, P.O.Box 14685

3M Romania,12 Menuetului St., Bucharest Business Park, Building D, District 1 013713 Bucharest, Romania

3M (East) AG, Representation Office Serbia, Airport City, Omladinskih brigada 90B, 11070 Belgrade, Serbia, Tel: +381 11 2209 400, www.3m.co.rs/3M/sr\_RS/3m-south-east-europe/

3M Slovensko s.r.o., Polus Tower 2, Vajnorská 100/B, 83104 Bratislava

3M (East) AG, Branch office Slovenia, Cesta v Gorice 8, 1000, Ljubljana, Slovenia, Tel: +386 1 2003 630, www.3m.com/3M/sl\_Sl/3m-south-east-europe/

3M Sanayi ve Ticaret As, Barbaros Mah., Mor Sümbül Sok., No:7/3F, 27-51, Nidakule Ataşehir Güney, 34746 Ataşehir, İstanbul, Turkey

3M Gulf Limited, Dubai Internet City, Building No. 11, 3rd Floor, U.A.E

3M España, S.L., sucursal em Portugal, Edifício Office Oriente, Rua do Mar da China Nº3 - Piso A, 1990-138 Lisboa, www.3m.com.pt/3M/pt\_PT/empresa-pt/ajuda/

© 3M 2024. 3M, Hookit and Trizact are all trademarks of the 3M company. All rights reserved