

Product Description

The 3M™ Melamine Floor Pad has been developed for cleaning and maintenance of hard floors. It is composed of a special melamine foam composite material that creates a profile structure for improved cleaning and dirt-absorption effects.

Applications

Use the 3M™ Melamine Floor Pad for routine maintenance procedures under standard low-speed floor machines (150 - 250 RPM).

It can be used under a single disc machine or a scrubber dryer in wet conditions (water or chemicals) to clean the floor.

Always make a trial in a corner or remote area first.



Features and benefits

- Cleans very well light black marks, light shoe marks, wheel marks, as well as grease and oil residues (such as sebum)
- Ideal for micro-porous surfaces such as ceramic, stoneware, terracotta, marble, terrazzo, polished and coated concrete, vinyl floors, etc. Ideal for swimming pools, changing rooms, shopping centers, and warehouses (typically ceramic or concrete floors)
- Also works well on plastics and linoleum, in health care buildings and schools (typically PVC floors and rubber floors)
- Cleans with very low abrasion on the floor
- Better cleaning performance and durability than conventional non-structured melamine pads
- Uneven structure of the pad goes around the irregularities of the floor, removing dirt with reduced clogging effect
- Use with water only or with a chemical to improve cleaning efficiency, like a neutral cleaner or a degreaser

Standard Size

Circular discs are available in a variety of common sizes.

Packaging and Marking

Each carton shall be labelled to identify the contents by product name, size, quantity, and manufacturer. Each pad shall be printed with a black 3M™ logo on the back side.

Characteristics

The values displayed are the results of illustrative lab test measures and shall not be considered as a commitment from 3M.

Characteristics	Value
Backing	White polyester fleece backing for improved grip under the machine
Weight	1400 g/m ²
Outer diameter dimensions	Designated Size ± 1.6 mm
Thickness	Approximately 30 mm Melamine: 25 mm / Fleece: 5 mm
Aggressiveness	Schiefer value = 0.08 g
Color	Grey and White Color may vary without impacting cleaning performance and durability

Pad Use

1. Install under the machine pad holder.
2. Wet scrub the area taking care enough liquid is available as 3M™ Melamine floor pad should not be used dry.
3. Remove pad and wash it after use.

Maintenance of the Pad

1. Remove the disc from the machine after each use.
2. Cleaning it under tap water.
3. Let it dry flat.

Note: Do not machine wash!

Durability

Durability highly depends on the floor structure and method of use.

- Under single disk machines (wet): 100 - 500 sqm
- Under scrubber-dryers (wet): 1000 - 5000 sqm
- Do not use strong acid or cleaning products containing chlorine

Storage

Storage conditions: +4°C to +40°C, out of sunlight, original container in a clean and dry indoor area.

Health and Safety

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety, and environmental information.

[Follow the link to obtain SDS sheets for 3M products on 3M.com/SDS.](https://www.3m.com/SDS)

[Follow the link to obtain information about substances of very high concern \(SVHC\).](#)

IMPORTANT!

- When using any equipment, always follow the manufacturer's instructions for safe operation.
- This floor pad is for professional or industrial use only.



DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:
DO NOT use this product on any asbestos-containing material.



WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:
Ensure this product is used in the recommended applications with the suggested equipment.

Do not allow this product to be used by untrained operators.

Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

To reduce the risks associated with environmental contamination:
Dispose of waste and slurries generated from wet polishing in accordance with all applicable local and government regulations.



CAUTION

The product is intended for wet floor maintenance processes only. DO NOT use this product in any dry application.

Warranty Information

Limited Remedy

This bulletin provides technical information only.

3M recommended product end uses are listed in each 3M product bulletin. End uses not listed in the applicable 3M Product Bulletins are typically not eligible for 3M Warranties. For non-recommended and/or non-warranted end uses or applications, users must test and approve the end uses or applications, assume any associated risks, and acknowledge that 3M has no liability for such end uses or applications. Please contact your 3M representative with any questions about applications, end uses, and warranties.

Limitations of liability

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

3M is a trademark of 3M. All other trademarks are the property of their respective owners.

3M United Kingdom PLC

Commercial Branding and Transportation
Cain Road
Bracknell, RG12 8HT
UK

© 3M 2025. All rights reserved.