



Science.
Applied to Life.™



Complex construction challenges made fast and easy.

3M™ Air Barrier with Permeable Backing 3015VP

This high-performing vapor permeable air barrier is designed to help control the indoor climate. Its Top Liner Technology reduces labor costs—just roll it, apply pressure, then peel off the liner. Plus, it's compatible with most building sealants and features excellent adhesion without the use of primer.



0 to 150°F

Application temperature



1 Person

Installation



No primer. No problem.

3M acrylic adhesive technology eliminates the need for primers

Let's Build Smarter.



Benefits

- No primer required on most common construction materials
- 40% faster installation when compared to air barriers requiring a primer
- Rain and wind-resistant; permeable to water vapor
- Application temperatures from 0° to 150°F (-18° to 66°C)
- Service temperature range from -40° to 240°F (-40° to 116°C)
- Industry-leading compatibility with many substrates and sealants
- Lightweight 100-foot rolls
- Class A Fire Rating, Passes NFPA 285 as part of various approved exterior wall assemblies
- ABAA Evaluated



Easy Application

Top Liner Technology with exposed adhesive and lightweight rolls allows for fast application and single-person installation.

Advanced Acrylic Adhesive

Exceptional pressure sensitive adhesive allows for immediate repositioning, with adhesion increasing over time resulting in strong and long-lasting bonds.

Built to Last

Up to 12-month UV exposure providing more flexibility for long-running projects or unexpected delays.

To learn more about how 3M can help you build smarter, please visit 3M.com/AirBarrier3015VP.



Industrial Specialties Division
3M Center, Building 225-3S-06
St. Paul, MN 55144 USA

Phone 1-866-513-4026
Web 3M.com/airbarriervp

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.

3M is a trademark of 3M Company. © 3M 2024. All rights reserved. Please recycle. Printed in USA.
70-0716-9844-6 Rev 7/24

Let's Build Smarter.

3M.com/BuildSmarter