



Technical Data Sheet

3M™ Value Duct Tape 1900

Product Description

3M™ Value Duct Tape 1900 is a conformable cloth duct tape made with polyethylene film over cloth scrim and rubber adhesive. A good choice for non-critical applications.

Product Features

- Polyethylene backing provides moisture resistance to tape applications.
- Rubber adhesive sticks well to many surfaces.
- Easy tear.
- Low profile.
- Individual roll wrap for easy identification.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Color		Silver
Adhesive Type		Synthetic rubber
Backing		Polyethylene over cloth scrim
Total Tape Thickness	ASTM D3652	0.147 mm

Typical Performance Characteristics

Attribute Name	Test Method	Temperature	Substrate	Value
180° Peel Adhesion	ASTM D3330, AFERA 5001	23 °C	Stainless Steel	6.8 N/cm ¹
Elongation at Break	ASTM D3759, AFERA 5004			20 % ¹
Tensile Strength	ASTM D3759, AFERA 5004			33 N/cm ¹
Long Term Temperature Resistance				93 °C ²

¹ 304 mm/min (12 in/min)

² Long Term (day, weeks)

Handling/Application Information

Application Examples

- Tool box tape for non-critical uses.
- Light duty sealing and holding.
- Marking.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 12 months from date of manufacture.

Available Sizes

Attribute Name	Value
Standard Roll Length	54.9 m
Standard Width	48, 72 mm

Information

Precautionary Information: Refer to product label and Material Safety Data Sheet for health and safety information before using the product. For information, please contact your local 3M Office. You can click or scan QR code to see contact detail or visit www.3M.com Important Information: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law. Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Centre
Cain Rd, Binfield, Bracknell RG12 8HT, United Kingdom
3m.co.uk/iatd

3M is a trademark of 3M Company.
©3M 2024 (9/24)