

3M™ Overlaminates for Exterior Walls

## Shield your graphics. Durable protection for lasting impressions.

Guard your graphics from the damaging effects of outdoor environments: rain, wind, and UV exposure. 3M overlaminates for exterior walls can help preserve the vibrancy of your brand messaging and helps ensure the graphic stays intact and visible over time, even when exposed to harsh outdoor conditions.

## Overlaminates for exterior walls

Products & Description	3M™ Scotchcal™ Overlaminate 8510M	3M <sup>™</sup> Scotchcal <sup>™</sup> Matte Graphic Protection Overlaminate 8520	3M™ Envision™ Wrap Overlaminates 8550M	3M <sup>™</sup> Scotchcal <sup>™</sup> Gloss Overlaminate 8528
Construction	3.5 mil non-cast PVC	2 mil cast PVC	2 mil non-PVC	2 mil cast PVC
Appearance	Matte	Matte	Matte	Gloss
Surface Type	Flat	Flat, Curved	Flat, Curved	Flat, Curved
Durability	Up to 4 years	Up to 8 years	Up to 9 years	Up to 9 years
Benefits	Protection against harsh conditions	Conformable & cleanable  Guards against scuffs, abrasion, UV  Protection against harsh conditions	Great for textured surfaces and smooth walls  Protection against harsh conditions  Minimizes reflection from lighting and sunshine	Protection against harsh conditions including UV, extreme heat, acid, dew  Strongest fading protection
Certifications	ASTM E84, UL 410 slip resistance	ASTM E84, UL 410 slip resistance	ASTM E84, UL 410 slip resistance, GREENGUARD Gold	ASTM E84
3M recommended films to pair with overlaminate*	40C, IJ46, IJ56C	IJ180mC, IJ180Cv3, "IJ3552C, "PL50mC	LX480mC, SV480mC	IJ180mC, IJ180Cv3
3M" MCS" Warranty  – 35 years and going strong —	-	Eligible	Eligible	Eligible

<sup>\*</sup>Confirm recommended applications with each 3M film.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a work-place hazard assessment, reviewing all applicable regulations and standards, and reviewing the product label and use instructions. Failure to properly evaluate, select, and use a 3M product in accordance with instructions or to meet all applicable safety regulations may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



<sup>\*\*</sup> Best for flat or slightly curved surfaces.