



## Technical Data Sheet

### Scotch® High Performance Fine Line Tape 4740



[Product Details](#)



[Regulatory Info/SDS](#)

#### Product Description

Scotch® High Performance Fine Line Tape 4740 is a highly conformable tape with a solventless acrylic adhesive system, used to achieve sharp paint lines and excellent clean removal. It has proven successful in high-temperature painting applications requiring a conformable tape. It is designed for use in two-tone automotive OEM paint masking applications.

#### Product Features

- Polyolefin backing is highly conformable and is PVC free.
- High temperature solventless acrylic adhesive is designed to remove cleanly with no edge residue or ghosting, this tape offers our best clean removal performance on most surfaces.
- Water-based adhesive reduces solvent use by 80% compared to similar 3M solvent based fine line tapes.
- Adhesive provides reliable holding power, adhering to complex surfaces without lifting.
- Heat resistant in bake cycles up to 180°C (356°F) for 10 minutes or 160°C (320°F) for up to 60 minutes. Remove warm at 70-150°F (21-65°C) for best results.
- High-temperature adhesive quickly sticks with confidence to most surfaces.
- Adheres to intricate surfaces and sharp curves for precise application.
- Sharp paint lines.

#### Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

#### Typical Physical Properties

Attribute Name	Test Method	Value
Color		Yellow
Adhesive Type		Acrylic
Backing		Polyolefin film
Total Tape Thickness	ASTM D3652	0.13 mm (5.2 mil)

#### Typical Performance Characteristics

Attribute Name	Test Method	Temperature	Test Condition	Value
180° Peel Adhesion	ASTM D3330	23 °C (73 °F)		2.3 N/cm (21 oz/in) <sup>1</sup>
Elongation at Break	ASTM D3759			1,353 %
Tensile Strength	ASTM D3759			42.7 N/cm (24.4 lb/in)
Temperature Use Range			Removable Application	160 °C (320 °F)
Temperature Use Range				180 °C (356 °F)
Temperature Use Range note				Up to 10 min for removable applications

<sup>1</sup> 304 mm/min (12 in/min)

## **Handling/Application Information**

### **Application Examples**

Ideal for two tone painting at automotive OEMs.  
Designed to handle high temperature applications and multiple bake cycles.  
Can be used for temporary protection of some metal, painted, plastic, and rubber surfaces.

### **Storage and Shelf Life**

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 12 months from date of manufacture.

### **Available Sizes**

Attribute Name	Value
Standard Roll Length	50 m (54.6 yd)

### **Information**

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

**Disclaimer:** 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit [www.3M.com](http://www.3M.com).

### **ISO Statement**

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division  
3M Center, St. Paul, MN 55144-1000  
[3M.com/iatd](http://3M.com/iatd)

Scotch is a registered trademark of 3M.  
©3M 2025 (7/25)