



3M™ Cubitron™ II Film Disc and Sheet Rolls 775L

3M I.D. Number	Cubitron™ II Film Disc 775L Cubitron™ II Film Disc On Roll 775L Cubitron™ II Film Sheet Rolls 775L											
Product Description	Abrasive product ideal for a broad range of applications focused on stock removal, scuffing, or finishing prior to coating or coating repair on multiple substrates: paints and other coatings, sealers, primer, gelcoat, composites, whitewood, and metals. Film backing for greater tear resistance and edge retention. Available with Hookit™ hook and loop attachment system or Stikit™ adhesive attachment system to fit end user needs.											
Mineral	Mineral: Aluminum Oxide and Ceramic Aluminum Oxide (Precision Shaped Grain) Grades Available: 80+, 120+, 150+, 180+, 220+, 240+, 320+, 400+, 500+, 600+, 800+, and 1000+											
Construction	Blend of Precision Shaped Grain ceramic aluminum oxide and crushed aluminum oxide mineral resin bonded to a 3 mil film backing. Hookit™ based product type have loops laminated to backing. Stikit™ based product type has adhesive laminated to backing. Various options for dust extraction hole patterns or no additional holes on disc.											
Dimensions	3", 5", and 6" discs standard stock availability, for other sizes available inquire as make-to-order products. Sheet Rolls standard stock sizing availability in 2.75 in x 13.1 yards and 4.5 in x 13.1 yards.											
Safety	<table border="1" data-bbox="561 1587 1390 1745"> <thead> <tr> <th data-bbox="561 1587 769 1625">Disc Size</th> <th data-bbox="769 1587 977 1625">3" (75mm)</th> <th data-bbox="977 1587 1185 1625">5" (127mm)</th> <th data-bbox="1185 1587 1390 1625">6" (152mm)</th> </tr> </thead> <tbody> <tr> <td data-bbox="561 1625 769 1745">Max Orbits Per Minute (OPM)</td> <td data-bbox="769 1625 977 1745">15000</td> <td data-bbox="977 1625 1185 1745">12000</td> <td data-bbox="1185 1625 1390 1745">12000</td> </tr> </tbody> </table> <p data-bbox="456 1791 1463 1898">Always use appropriate PPE and follow safety precautions as instructed in the associated Product Safety Insert. Product Safety Inserts are included with shipped product and are also available on-line through 3M.com.</p>				Disc Size	3" (75mm)	5" (127mm)	6" (152mm)	Max Orbits Per Minute (OPM)	15000	12000	12000
Disc Size	3" (75mm)	5" (127mm)	6" (152mm)									
Max Orbits Per Minute (OPM)	15000	12000	12000									

IMPORTANT NOTICE TO PURCHASER:

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (*e.g.*, OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Abrasive Systems Division
3M Center Building 240-1-01
Saint Paul, MN 55144

1-866-279-1235
www.3M.com/abrazives

3M is a trademark of 3M.
Please recycle. © 3M 2025. All rights reserved.