

Product Description

3M™ Blue Cleaner Pad 5300 is a floor maintenance cleaning and scrubbing pad made of nylon and polyester fibers in an open textured, non-woven construction. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable resin system that permeates the entire pad. Unique design and durable construction make these pads the industry standard for consistent performance and long life.

- Designed for use with detergent solution to scrub coated floors
- For use on standard, low speed automatic scrubbers and rotary floor machines (175 - 600 rpm)



Applications

This product is used with detergent solution for regular cleaning and scrubbing of hard surface floors. The product is also used for dry scrubbing floors and for heavy duty spray cleaning. The product is intended for use on standard, low speed automatic scrubbers and rotary floor machines.

For use on finish-coated flooring such as sheet vinyl, vinyl tile, marble, terrazzo or concrete.

Features and Benefits

Uniform coating throughout every 3M™ floor pad reduces the number of knots and clumps, which eliminates scratching of floors while providing greater consistency and extended pad life.

Pads are reversible and will not be significantly affected by water, detergents, or cleaners normally used for floor maintenance.

Exact standards for quality mean thickness uniformity from edge to edge and pad to pad are exceptional, resulting in consistent performance without pad wobbling or machine vibration. The precise center-hole placement and roundness of the pads also contribute to the smooth operation which extends pad life and may help reduce operator fatigue.

Pad Use and Cleaning

Dust mop or sweep floors prior to scrubbing. Pick up scrubbing or cleaning solution with a mop, wet vacuum, or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent solution to dissolve caked soil or finish prior to hosing out.

Standard Size

Circular discs are available in a variety of common sizes.

Packaging and Marking

Each carton shall be labeled to identify the contents by product name, size, quantity and manufacturer. Each pad shall be printed with the manufacturer's name.

Storage

Storage conditions: +4°C to +40°C, out of sunlight, original container in a clean and dry indoor area.

Characteristics

The values displayed are the results of illustrative lab test measures and shall not be considered as commitment from 3M.

Characteristics	Value
Fiber type	Nylon/Polyester blend
Weight	1450 g/m ²
Outer diameter dimensions	Designated Size ± 1.6 mm
Thickness	Approximately 25 mm
Aggressiveness	1.8 g*
Color	Blue
Packaging Recycle Content	50 – 100% recycled content

*Schiefer test on acrylic plate material (after 5000 revolutions with a new pad)

Health and Safety

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety, and environmental information.

[Follow the link to obtain SDS sheets for 3M products on 3M.com/SDS.](#)

[Follow the link to obtain information about substances of very high concern \(SVHC\).](#)

IMPORTANT! When using any equipment, always follow the manufacturer's instructions for safe operation.



DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:

DO NOT use this product on any asbestos-containing material.



WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

To reduce the risks associated with environmental contamination:

- Dispose of waste and slurries generated from wet polishing in accordance with all applicable local and government regulations.



CAUTION

Product is intended for wet floor maintenance processes only. DO NOT use this product in any dry application.

Warranty Information

Limited Remedy

This bulletin provides technical information only.

3M recommended product end uses are listed in each 3M product bulletin. End uses not listed in the applicable 3M Product Bulletins are typically not eligible for 3M Warranties. For non-recommended and/or non-warranted end uses or applications, users must test and approve the end uses or applications, assume any associated risks, and acknowledge that 3M has no liability for such end uses or applications. Please contact your 3M representative with any questions about applications, end uses, and warranties.

Limitations of liability

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

3M is a trademark of 3M. All other trademarks are the property of their respective owners. The use of trademark signs and brand names in this bulletin is based on US standards. These standards may vary from country to country outside the USA.

3M United Kingdom PLC
Commercial Solutions Division
Cain Road
Bracknell, RG12 8HT
UK

3M Ireland Ltd.
The Iveagh Building
The Park, Carrickmines
Dublin 18
Ireland

© 3M 2026. All rights reserved.