

Description

3M Graffiti Removers are designed for maximum effect to remove aerosol spray paints, felt pen inks, emulsion paints, lipstick and crayon from their recommended surface type.

- GR1500 is formulated to remove safely and effectively graffiti from most plastic surfaces and from most painted or varnished surfaces without damaging or harming them.
- GR3000 is formulated to remove graffiti effectively from brickwork and concrete surfaces.

Applications

Use GR1500 on: Most Plastics, Plastic Laminates, Flat Unstressed Polycarbonate Sheeting, Clear Acrylic Surfaces, Some Vinyl, Gloss Painted Surfaces, Varnish Surfaces, Latex Paints.

Use GR3000 on: Brickwork, Concrete, Metallic Surfaces, Stainless Steel, Vitreous Enamel, Ceramic Tile.

Properties

- Liquid form allows a quick penetration and a fast break-down of the graffiti.
- Low odour
- Uses biodegradable raw materials, does not contain aromatic, aliphatic or chlorinated solvents, very low environmental impact
- Neutralised with water.
- Available in spray bottle 0.5L or 5 L container.

Directions for Use

1. For best results spray onto the graffiti and leave up to five minutes before agitating with a cloth or brush. Another method is to dampen a clean Scotch-Brite™ 350 or a 3M Scotch-Brite™ microfiber wipe such as Scotch-Brite™ 2010 High Performance cloth with the liquid. Dab and wipe off the graffiti, turning the cloth frequently to ensure the mark is not returned to the surface.
2. Wipe off any residue with a clean damp Scotch-Brite™ 350 or a 3M Scotch-Brite™ microfiber wipes such as Scotch-Brite™ 2010 High Performance cloth then rinse the surface, for best results wash with a mild detergent.
3. If preferred, apply the liquid with a soft brush then continue agitating to remove the graffiti.
4. Ensure that the surface is kept wet, if necessary, reapply the liquid. Wipe and rinse as above. Do not skip rinsing with water at the end of the job.

Notes

Test on a small area prior to complete coverage to check for surface compatibility.

The graffiti removal action will stop once rinsed with water.

Product may have a limited effect on aged graffiti which may have already damaged the surface.

Product characteristics

		GR1500	GR3000
Boiling point		>100°C	
Flash point		100°C	
Density		0.97	1.04

Packaging

- 4 spray bottle 500 ml per case
- 4 containers 5 Liters per case.

Shelf Life

The shelf life is 2 years after manufacturing date for unopened containers.

Manufacturing date is printed below the bottle/container.

Once the container has been opened the maximum storage life is 1 year.

Health and Safety

Tools and Equipment Usage

When using any equipment, always follow the manufacturer's instructions for safe operation.

Chemicals

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety, and environmental information.

[Follow this link to obtain SDS sheets for 3M products.](#)

[Follow this link to obtain information about substances of very high concern \(SVHC\) for EU products.](#)

Warranty Information

Technical Information

Technical information, guidance, and other statements provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license to any intellectual property rights is granted or implied with respect to this technical information.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment, reviewing all applicable regulations and standards, and reviewing the product label and use instructions. Failure to properly evaluate, select, and use a 3M product in accordance with instructions or to meet all applicable safety regulations may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.